

Micro Commercial Components

Features

- High Surge Capability
- Ver low forward voltage drop Halogen free available upon request by adding suffix "-HF"
- Low power losses, high efficiency
- Guardring for overvoltage protection
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -55°C to +125°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 14°C/W Junction To Lead
 - 50°C/W Junction To Ambient

Rohs

Phone: (818) 701-4933

Micro Commercial Components

20736 Marilla Street Chatsworth

(818) 701-4939

COMPLIAN

CA 91311

Fax:

MCC Catalog Number	Device Marking	Maximum Reccurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SK42L	SK42L	20V	14V	20V
SK43L	SK43L	30V	21V	30V
SK44L	SK44L	40V	28V	40V

Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward	I _{F(AV)}	4.0A	T _L = 90°C
Current			
Peak Forward Surge	I _{FSM}	150A	8.3ms, half sine
Current			
Maximum Instantaneous Forward Voltage*	Vf	.45V	I _{FM} = 4.0A;T _A =25°C
Maximum DC Reverse Current At Rated DC Blocking Voltage*	I _R	0.5mA 35mA	T _A = 25°C T _A = 100°C

*Pulse test: Pulse width 300 µsec, Duty cycle 1%


Notes: 1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

SK42L THRU SK44L

4 Amp Schottky Rectifier 20 to 40 Volts



DIMENSIONS						
	INCHES		MM			
DIM	MIN	MAX	MIN	MAX	NOTE	
A	.260	.280	6.60	7.11		
В	.220	.245	5.59	6.22		
С	.006	.012	0.15	0.31		
D	.030	.060	0.76	1.52		
E	.305	.320	7.75	8.13		
F	.079	.103	2.00	2.62		
G	.108	.128	2.75	3.25		
н	.002	.008	0.050	0.203		



www.mccsemi.com

SK42L thru SK44L



(T_A = 25 °C unless otherwise noted)




Figure 1. Forward Current Derating Curve






Figure 3. Typical Instantaneous Forward Characteristics












Figure 5. Typical Junction Capacitance

www.mccsemi.com

2 of 3



Ordering Information :

Device	Packing	
Part Number-TP	Tape&Reel: 3Kpcs/Reel	

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com

Revision: C

2014/03/07