



# CM7V-T1A

## Tuning Fork Crystal 32.768 kHz



### DIMENSIONS



### APPLICATIONS

IoT  
 Metering  
 Industrial  
 Automotive  
 Health Care  
 Wearables, Portables

### DESCRIPTION

The CM7V-T1A is a low frequency SMT Quartz Crystal Unit that incorporates a tuning fork Quartz Crystal Resonator. It operates under vacuum in a hermetically sealed ceramic package with metal lid.

### FEATURES

Outstanding hermetic sealing with gold-tin preform.  
 High stability and low aging guaranteed by hermetic sealing.  
 Available for extended operating temperature range.  
 Small size, low profile, lightweight (10.3 mg).  
 High shock and vibration resistant.  
 100% Pb-free, RoHS-compliant.  
 Automotive qualification according to AEC-Q200 available.

### ELECTRICAL CHARACTERISTICS AT 25°C

Standard Frequencies 32.768 kHz / 100.000 kHz <sup>1)</sup>	F <sub>L</sub>	32.768	kHz
Load capacitance <sup>2)</sup>	C <sub>L</sub>	6.0 / 7.0 / 9.0 / 12.5	pF
Frequency tolerance <sup>3)</sup>	ΔF/F	±20	ppm
	ΔF/F	±100	ppm
Series resistance typ./max.	R <sub>S</sub>	50 / 70	kΩ
Motional capacitance typ.	C <sub>1</sub>	3.7	fF
Static capacitance typ.	C <sub>0</sub>	1.2	pF
Drive level max.	P	1.0	μW
Insulation resistance min.	R <sub>i</sub>	500	MΩ
Aging first year max.	ΔF/F	±3	ppm
Turnover temperature	T <sub>0</sub>	25 ±5	°C
Frequency vs. temperature	ΔF/F <sub>0</sub>	-0.035 ppm/°C <sup>2</sup> (T - T <sub>0</sub> ) <sup>2</sup> ±10%	

- 1) Other frequencies on request.
- 2) Other load capacitances on request.
- 3) Tighter frequency tolerances on request.

## STANDARD FREQUENCIES

Frequencies
32.768 kHz / 100.000 kHz
Other frequencies on request

## ENVIRONMENTAL CHARACTERISTICS

		Conditions	Max. Dev.
Storage temp. range		-55 to +125°C	
TA Operating temperature range		-40 to +85°C	
TB Extended oper. temp. range		-40 to +125°C	
TC Extended oper. temp. range		-55 to +125°C	
Shock resistance	ΔF/F	5000 g, 0.3 ms, ½ sine	±5 ppm
Vibration resistance	ΔF/F	20 g / 10–2000 Hz	±5 ppm

## TERMINATIONS AND PROCESSING

Type	Termination	Processing
CM7V-T1A	For SMT mounting Au flashed pads	IPC/JEDEC J-STD-020C 260°C / 20 - 40 s

## ORDERING INFORMATION

	C	M	7	V	-	T	1	A	32.768 kHz	12.5 pF	±20 ppm	TA	QC
<b>Ceramic package</b>													
<b>Metal lid</b>													
<b>Package size</b> 7 = 3.2 x 1.5 x 0.65 mm													
<b>Tuning fork</b>													
<b>SMT Package</b>													
<b>Au flashed pads</b>													
<b>Pads on both ends</b>													
									<b>Frequency <math>F_L</math></b>				
									<b>Load capacitance <math>C_L</math></b>				
									6.0 pF				
									7.0 pF				
									9.0 pF				
									12.5 pF				
									Other $C_L$ on request				
									<b>Frequency tolerance</b>				
									±20 ppm				
									±100 ppm				
									Tighter freq. tolerances on request				
									<b>Temperature range</b>				
									TA = -40 to +85°C (Standard)				
									TB = -40 to +125°C				
									TC = -55 to +125°C				
									<b>Qualification</b>				
									QC = Commercial Grade (Standard)				
									QA = Automotive Grade AEC-Q200				
A unique part number will be generated for each product specification, i.e.:													
20xxxx-MG01	1'000 pcs (in 12 mm tape on 7" reel)												
20xxxx-MG03	3'000 pcs (in 12 mm tape on 7" reel)												
20xxxx-PG14	14'000 pcs (in 12 mm tape on 13" reel)												

All specifications subject to change without notice.



Micro Crystal AG  
Muehlestrasse 14  
CH-2540 Grenchen  
Switzerland

Phone +41 32 655 82 82  
Fax +41 32 655 82 83  
sales@microcrystal.com  
www.microcrystal.com