

接线图  
Wiring Diagram

连接器针位 vs. 引线颜色  
Pin No. vs. Lead Wire Colour

Pin No.	颜色 Colour
1	黑 Black
2	橙 Orange
3	红 Red
4	蓝 Blue

励磁顺序 vs. 旋转方向  
Exciting Sequence vs. Direction of Rotation


STEP	A	B	C	D	CCW
1	+	+	-	-	CW
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	

从安装面看为顺时针方向  
Clockwise view from mounting side

规格 Specifications

1. 相数 Number of Phase	2
2. 步距角 Step Angle	0.9°
3. 额定电压 Rated Voltage	3.54V DC
4. 额定电流 Rated Current	0.3Amp
5. 保持力矩 Holding Torque	85mNm Typ. (Two phase on/rated current)
6. 相电阻 Phase Resistance	11.8ohm±10%(20°C)
7. 相电感 Phase Inductance	9.5mH±20%(1kHz 1V rms)
8. 转子惯量 Rotor Inertia	119cm <sup>2</sup>
9. 电机重量 Motor Weight	0.11kg
10. 绝缘等级 Insulation Class	B(130°C)

铭牌 Label Detail



MOONS'		Hybrid Stepping Motor	
Shanghai Moons' Electric Co., Ltd.		This document is released for information only. Its reproduction in whole or in part or its dissemination to third parties is prohibited. All trademarks and registered trademarks appearing on this document are the property of their respective owners.	
批准 Approve	标准化 Standard	工艺 Technology	审核 Check
设计 Design	NAMES	SIGNATURE	DATE
2019.05.07	艾志威	艾志威	2019.05.07
REV.	版本记录 REVISION RECORD	REV.A	SCALE 1:1
A	原始版本 Original revision	14HK2405-11N	Sheet 1 of 1