

- Up to 87% efficiency
- High power density
- Remote on/off
- 5V Standby output (1amp)
- Universal AC input
- Active PFC (90 – 264 VAC)
- Inrush current protection
- RoHS compliant



XL260-2ATX Model shown

**Power Supply Design Leader**

N2Power™ leads the power density race with its small, high efficiency ATX Series AC-DC power supplies. Our advanced technology yields a very small footprint, reduces wasted power and offers the highest power density in its class. This efficient design means reduced energy costs, a greater return on your investment, greater reliability and longer product life.

**Unmatched Power Density**

Our ATX Series models are designed expressly for OEM packaging in 1U and 2U chassis to deliver very high power density. The XS285-ATX model features multiple outputs and cooling in an industry standard enclosure for PC chassis applications.

**High Efficiency in a Small Package**

The ATX Series provides up to 87% efficiency. Our unique design reduces energy consumption and generates less wasted heat.

It requires little forced air cooling, decreases AC loading, and increases reliability and economy of operation. Comparisons of efficiencies show that our supplies can reduce losses up to 50%.

**Repeatable Quality**

Each power supply design is tested by UL, and every one we manufacture undergoes a complete functional test and a multi-hour burn-in to insure that every unit meets our stringent quality requirements.

**Models and Dimensions (W x D x H)**

XL125-1ATX	XL160-1ATX	XL160-7ATX	XL160-8ATX	XL220-1ATX	XL260-2ATX	XL260-4ATX	XS285-ATX
3 x 5 x 1.25" 76.2 x 127 x 31.7mm	3 x 5 x 1.25" 76.2 x 127 x 31.7mm	3 x 5 x 1.25" 76.2 x 127 x 31.7mm	3 x 5 x 1.25" 76.2 x 127 x 31.7mm	3 x 5 x 1.3" 76.2 x 127 x 33mm	3 x 5.3 x 1.35" 76.2 x 134.6 x 34mm	3 x 5.3 x 1.35" 76.2 x 134.6 x 34mm	5.5 x 5.9 x 3.4" 139.7 x 149.9 x 86.4mm

Contact us regarding custom supplies for unique applications



MODEL	PART NUMBER	OUTPUT	VOLTAGE	REGULATION (%)	MAXIMUM CURRENT (A)	RIPPLE & NOISE (P-P)
XL125-1ATX	400002-71-3	V1	3.3	±2	10.0	50 mV
		V2	5	±4	15.0	50 mV
		V3	12	±5	5.0	120 mV
		V4	-12	±5	1.0	120 mV
		V5	5sb	±5	1.0	50 mV
XL160-1ATX	400011-04-5	V1	3.3	±2	15.0	50 mV
		V2	5	±4	20.0	50 mV
		V3	12	±5	6.0	120 mV
		V4	-12	±5	1.0	120 mV
		V5	5sb	±5	1.0	50 mV
XL160-7ATX	400017-02-6	V1	2.5	±2	15.0	50 mV
		V2	5	±4	20.0	50 mV
		V3	12	±5	6.0	120 mV
		V4	-12	±5	1.0	120 mV
		V5	5sb	±5	1.0	50 mV
XL160-8ATX	400018-07-3	V1	5	±4	20.0	50 mV
		V2	12	±5	6.0	120 mV
		V3	-12	±5	1.0	120 mV
		V4	5sb	±5	1.0	50 mV
		V5	5sb	±5	1.0	50 mV
XL220-1ATX	400019-01-4	V1	24	±4	6.0	240 mV
		V2	5	±4	10.0	50 mV
		V3	12	±5	1.0	120 mV
		V4	12	±5	1.0	120 mV
		V5	5sb	±5	1.0	50 mV
XL260-2ATX	400050-02-7	V1	24	±4	6.0	240 mV
		V2	5	±4	10.0	50 mV
		V3	12	±5	4.0	120 mV
		V4	12	±5	0.7	120 mV
		V5	5sb	±5	1.0	50 mV
XL260-4ATX	400050-04-3	V1	48	±4	3.0	480 mV
		V2	5	±4	10.0	50 mV
		V3	12	±5	4.0	120 mV
		V4	12	±5	0.7	120 mV
		V5	5sb	±5	1.0	50 mV
XS285-ATX	400027-01-7	V1	3.3	±2	15.0	50 mV
		V2	5	±4	20.0	50 mV
		V3	12	±5	6.0	120 mV
		V4	-12	±5	1.0	120 mV
		V5	5sb	±5	1.0	50 mV
		V6	24	±3	5.2	240mV
		V7	12	±5	1.0	120 mV

INPUT SPECIFICATIONS	
Nominal Input Voltage:	100 – 240 VAC
Tested Input Limits:	90 – 264 VAC
Input Frequency Range:	47 – 63 Hz
Input Current:	See Product Specification
Safety Isolation:	3000 VAC in to out 1500 VAC in to ground
Inrush Current:	See Product Specification
Leakage Current:	0.75 – 1.4 mA @ 240 VAC / 60 Hz
Power Factor Correction:	Active PFC circuitry, meets or exceeds EN61000-3-2
OUTPUT SPECIFICATIONS	
Total Output:	125W – 285W
Hold-up Time:	Minimum 22 ms
Efficiency:	Up to 87%
Minimum Load:	No load
Over / Under Shoot:	Max 10% at turn-on
PROTECTION	
Input Overcurrent Protection:	See Product Specification
Overvoltage Protection:	V1, V2 and V3 (latches off)
Overpower Protection:	Protected / Auto-recovery
Short Circuit Protection:	Auto recovery of all outputs protected against short circuit
Thermal Shutdown:	Auto recovery protection against over temperature conditions
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature:	-25 to +50°C
Temperature Derating:	2.5% / degree, 50°C to 70°C
Storage Temperature:	- 40 to +85°C
Forced Air Cooling:	10 CFM minimum *
MTBF:	>200,000 hours (calculated)
SIGNALS	
Remote Sense	See Product Specification
Fan Output	See Product Specification
Remote Enable Input	Low-true input
Power Good	Positive true

\* XS285-ATX contains fan

### Compliance <sup>1</sup>

#### USA / Canada

**Safety:** UL 60950-1:2007 (2<sup>nd</sup> Edition) / C22.2 No. 60950-1-07  
UL 62368-1 (Second Edition)  
Safety of Information Technology Equipment (ITE)

**EMC:** FCC part 15, subpart B

#### Europe

2006/95/EC - "Low Voltage (Safety) Directive"  
Demko: EN 60950-1:2006+A11:2009 (2nd Edition)  
EN 62368-1:2014 / A11:2017

2004/108/EC "Electromagnetic Compatibility (EMC) Directive" EN 61204-3 Class B

#### International

EC 60950-1:2005 (2nd Edition)  
IEC 62368-1:2014  
Safety of Information Technology Equipment

IEC 61204-3 Class B

<sup>1</sup> See Product Specification for additional information. The power supply is considered a component of the final product in which it is being used. The final product itself must be tested separately for compliance with all applicable standards.

Every effort has been made to keep the information contained in this document current and accurate as of the date of publication or revision. However, no guarantee is given or implied that the document is error-free or that it is accurate with regard to any specification. N2Power reserves the right to change specifications without notice. Qualstar and the Qualstar logo are registered trademarks of Qualstar Corporation. N2Power and the N2Power logo are trademarks of Qualstar Corporation. All other trademarks are the property of their respective owners.

