


Takutiru JB-15FBP2

This page is product introduction page.

For those who wish to purchase or download various types, please search the product name for product name.

Tactile switch (JB series) · PC terminal type: Single pole single throw · Operation part: Flat type · Operating power: General type (1.8 N) · Reliable operation feeling · Terminal shape same as IC · Space saving Washes possible for PC board · Washable with washing · Operating temperature range: -25 to 70 °C · RoHS compliant (from shipping on July 1, 2006)



The photograph is a sample image. The color and shape may differ from the actual one. Please be sure to confirm the actual color and shape with product samples etc.

Product information

- [New product information](#)
- [Product Search](#)
- [Product list](#)
- [e order \(set kit item selection\)](#)

- [For safe use](#)
- [RoHS Directive](#)
- [Spec List](#)



Please use the latest browser in order to use the function of this site. CAD downloading etc. may not work on browsers below IE 10.

■ Product overview

| | |
|---|--|
| Model name | JB-15FBP2 |
| category | Tactir |
| series | JB |
| Subcategory | Non-illuminated type |
| Search current capacity | Small current area |
| Contact specification | Silver plating |
| Detailed display current capacity 1 | 50 mA 24 V DC |
| Operating temperature range (° C) | -25 / + 70 |
| Number of poles | Monopole |
| Function 1 | OFF- (ON) |
| Operation part shape | Round: 7 |
| Terminal part shape | Printed circuit board straight |
| Dimensions Reference 1 (Unit: mm vertical * horizontal * back) | 4.2 × 10 × 10 |
| Dimensions of External Dimensions 2 (Condition) | Except for the operation section, the height is the upper surface of the board |
| Operating part dimensions | 0.7 × 7 Dia. |

| | |
|----------------------------------|------|
| standard 1 (Unit: mm) | |
| Environmental performance | RoHS |