

## Product Overview

### AR0230AT: CMOS Image Sensor, 2 MP, 1/3"

For complete documentation, see the data sheet.

The AR0230AT is a 1/2.7-inch CMOS digital image sensor with an active-pixel array of 1928Hx1088V. It captures images in either linear or high dynamic range modes, with rolling-shutter readout. It includes sophisticated camera functions such as in-pixel binning, windowing and both video and single frame modes. It is designed for both low light and high dynamic range scene performance. It is programmable through a simple two wire serial interface. The AR0230AT produces extraordinarily clear, sharp digital pictures, and its ability to capture both continuous video and single frames makes it the perfect choice for a wide range of applications.

### Features

- High Dynamic Range

### Applications

- Automotive

### Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Type	Megapixels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
AR0230ATSC00XUEA0-DRBR		AEC Qualified PPAP Capable Pb-free Halide free	Active	CMOS	2.1	30	1/2.7 inch	Global Reset Release Electronic Rolling	3.0 x 3.0	Parallel HiSPi™	RGB	IBGA-80
AR0230ATSC00XUEA0-DRBR-E		Pb-free Halide free	Active	CMOS	2.1	30	1/2.7 inch	Electronic Rolling and Global Reset Release	3.0 x 3.0	Parallel HiSPi™	RGB	IBGA-80
AR0230ATSM00XUEA0-DRBR-E		Pb-free Halide free	Active	CMOS	2.1	30	1/2.7 inch	Electronic Rolling and Global Reset Release	3.0 x 3.0	Parallel HiSPi™	Mono	IBGA-80

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com).

Created on: 5/27/2020