

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click  to remove) [Search Tips](#)

 **Text Search: 'CD9-5B'**


Your search criteria matched only one product, shown below

CD9-5B



Reel Smart™ Installation Requirements.

All tooling information, including crimp shut height dimension, is included on the product reel label.

| | |
|-------------------------------|---|
| Part Number | CD9-5B |
| RoHS Compliancy Status | RoHS directive is not applicable |
| Part Description | Die Insert for CA9 Applicator |
| 60/40 Solder Slug Dia. (In.) | .188 |
| 60/40 Solder Slug Dia. (mm) | 4.78 |
| CE Compliant | No |
| CE Marking | No |
| Panduit Color Code | Blue |
| Pricing Description | Die Insert, for use with CA9 Applicator, to terminate PANDUIT reeled disconnects |
| Wire Insulation Strain Relief | Insulation Support |
| Wire Range | 16 – 14 |
| Wire Range (mm ²) | 1.5 – 2.5 |
| Min. Order UOM | PC |
| Min. Order Qty. | 1 |
| BOM Qty. (# of Pkgs.) | <input type="text" value="0"/> |
| Add to Favorite Product List |  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.