THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. PANDUIT P/N WEIGHT (APPROX.) ______ 17**.**42 [442**.**5] -.79 -DPKR245E88TG | 1.437 LB (651.7 g) [20.1] NOTES: RETENTION CAP SNAPS ONTO CONNECTOR 1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AS_WELL AS OPTIONAL ICONS. 2. KIT INCLUDES THE FOLLOWING: 1 - LABEL SET 1-24 BLANK LABEL 1.17 [29.6] 5 - LABEL HOLDERS 0C+ C UL US LISTED STRAIN RELIEF BAR DP5e 24 PORT PATCH PANEL 8 - 12-24 X 1/2" ROUND HEAD SCREWS 4 - M6×1 X 15mm METRIC SCREWS 3. MATERIAL: PANEL HOUSING: STEEL RJ45 MODULE: THERMOPLASTIC RESIN UL94V-0 PUNCHDOWN BLOCKS: THERMOPLASTIC RESIN UL94V-O BEZEL ASSEMBLY: THERMOPLASTIC RESIN UL94H-B RETENTION CAP: THERMOPLASTIC RESIN UL94V-O — 18**.**44 [468**.**4] STRAIN RELIEF BAR: STEEL BAR STOCK LABEL: VINYL LABEL HOLDER: CLEAR VINYL MOUNTS TO 19" UNIVERSAL RACKS -4. 24 PORT PATCH PANEL 8 POSITION 8 WIRE. 5. THE PATCH PANEL AND STRAIN RELIEF BAR ARE - 3**.**65 [92**.**7] 1.25 DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS. 6. DIMENSIONS IN PARENTHESES ARE IN METRIC. [31.8] 7. USE 110 STYLE TERMINATION TOOL FOR PUNCHDOWN. 8. RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS. .40 1.72 -[10.2] [43.7] .28 CID**-C & CIP**-C, PHONE OR DATA ICON LOCATED HERE, IDENTIFIES [7.1] 1.25 -INDIVIDUAL PORT, OPTIONAL, NOT SUPPLIED. [31.8] SIZE DRAWING FILENAME M01537EL_DC51_00A.PRT DP5e 24 PORT PATCH PANEL DP5E 24 PORT PATCH PANEL WITH STRAIN RELIEF BAR AND LABEL KIT CUSTOMER DRAWING I.I. NUMBER PANDUIT CORP. PRODUCT SPEC/ PKG SPEC TINLEY PARK, ILL 60477 ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED. ASSY METHOD/ TEST METHOD DIMENSIONAL TOLERANCES ARE: SCALE (.X) ±.03 (.XXX) ±.005 (.XX) ±.01 ANGLES ± 1° THIRD ANGLE NONE PART NO. REVIEW DRAWING NUMBERS BJN SEE CHART RELEASE TO PRODUCTION 01537-51 11/26/07 11/26/07 BJN RJDU VMB MAT'L 01537-51 RJDU DATE SUP BY CHK DESCRIPTION ECN - R CUST SHEET 1 OF 2

