

Search Results

Evaluate

- FAQ's

Design a Solution

- Part Drawings
- PDF Fiber Optic ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results


 Text Search: 'F5D2-2M1'

Your search criteria matched only one product, shown below

F5D2-2M1Y



- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode patch cord
- Lifetime traceability of test data to a Q.C. number on each patch cord
- SC Duplex Patch Cords include SC Duplex Clips to maintain polarity
- Highest quality flame retardant fiber optic cable with tight -buffered coating on each optical fiber

Part Number	F5D2-2M1Y
RoHS Compliancy Status	Compliant
Note	F5D2-2M1Y replaces F5D2-2M1
Part Description	ST to ST multimode duplex patch cord, 3mm jacketed cable (two ST connectors on each end) - 50/125µm.
Product Type	ST Patch Cords
Length (m)	1
Fiber Compatibility	50/125µm
Fiber Cable Size	3mm
Fiber Cable Type	Jacketed
Fiber Type	Multimode
Connector 1 Type	ST Connector
Connector 2 Type	ST Connector
End Configurations	ST to ST
Fiber Count	2
Flammability Rating	Riser (OFNR)
Pricing Description	ST-ST 50µm Dupl 3mm 1m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.