

Search Results

- Evaluate
  - FAQ's
- Design a Solution
  - Part Drawings
  - PDFPre-Terminat ..
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'F66D2-NM2Y'


Your search criteria matched only one product, shown below

**F66D2-NM2Y**



Fan-Out Cords – Multimode 62.5/125 μm (OM1)

- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Pigtailed (open) end allows quick high performance field fusion splice during installation to provide the lowest installed cost
- 900 μm tight-buffered fibers break out to terminated colored buffers for quick and easy identification of separate channels for accurate installations
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode fan -out cord
- Lifetime traceability of test data to a Q.C. number on each fan -out cord
- Highest quality flame retardant fiber optic cable with tight -buffered coating on each optical fiber

Part Number	F66D2-NM2Y
RoHS Compliancy Status	Compliant
Note	F66D2-NM2Y replaces F66D2NM2
Part Description	ST to pigtail 6fiber fan-out cord (six ST connectors on one end and open on the other end on distribution cable)– 62.5/125μm.
Product Type	Fan-Out Cords
Length (m)	2
Fiber Compatibility	62.5/125μm
Fiber Type	Multimode
Connector 1 Type	ST Connector
Connector 2 Type	Pigtail
End Configurations	ST to Pigtail
Fiber Count	6
Flammability Rating	Riser (OFNR)
Pricing Description	PC 6Fiber mm 6 STOpen 62.5μ m 2m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.