

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'F6D4-4M1Y'

Your search criteria matched only one product, shown below

F6D4-4M1Y



- Pass all TIA/EIA-568-B.3 performance requirements
- Insertion loss per connection: 0.10dB typical; 0.30dB maximum
- Factory terminated and 100% tested for insertion loss
- Insertion loss data recorded for every multimode patch cord
- Lifetime traceability of test data to a Q.C. number on each patch cord
- SC Duplex Patch Cords include SC Duplex Clips to maintain polarity
- Highest quality flame retardant fiber optic cable with tight -buffered coating on each optical fiber

Part Number	F6D4-4M1Y
RoHS Compliancy Status	Compliant
Note	F6D4-4M1Y replaces F6D4-4M1
Part Description	FC to FC multimode duplex patch cord (two FC connectors on each end)- 62.5/125µm.
Product Type	FC Patch Cords
Length (m)	1
Fiber Compatibility	62.5/125µm
Fiber Cable Size	3mm
Fiber Cable Type	Jacketed
Fiber Type	Multimode
Connector 1 Type	FC Connector
Connector 2 Type	FC Connector
End Configurations	FC to FC
Fiber Count	2
Flammability Rating	Riser (OFNR)
Pricing Description	PC FC To FC 62.5µm Dupl mm 1m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.