




THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



NOTES:

1. SEE SHEET 2 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS.
2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY.
3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON.
4. TESTED TO EIA/TIA 568-B.3.
5. PATCH CORD ROUTING CONFIGURATION A TO B.
6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.

										FIBER OPTIC PATCH CORD FJ OPTI-PLUG TO ST CONFIGURATION CUSTOMER DRAWING		
										 <b>PANDUIT</b> <sup>TM</sup> CORP. TINLEY PARK, ILL 60477		
										 THIRD ANGLE PROJECTION		
										ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.X) (.XXX) ± .010 (0.3) (.XX) ± .03 (0.8) ANGLES		
										DRAWING FILENAME M02779BJ_DC_00A.prt SCALE NONE		
										PART NO. SEE TABLE, SHT. 2 DRAWING NO. 02779-16 (SHT. 1 of 2)		
										SIZE A		
R	06-05-07	MC		RELEASED TO PRODUCTION	02779-16						DRAWN BY MC DATE 05-10-07 CHK'D	REVIEW DRAWING NUMBERS PART NO. SEE TABLE, SHT. 2 DRAWING NO. 02779-16 (SHT. 1 of 2)
REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH			

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



FJ OPTI-PLUG TO ST FIBER OPTIC PATCH CORD

PANDUIT PART NO.	CABLE				FJ OPTI-PLUG			ST CONNECTOR		
	RATING	FIBER TYPE	COUNT	COLOR	MAX. IL	MIN. RL	COLOR	MAX. IL	MIN. RL	COLOR
F5D6P-2M*Y	RISER (OFNR)	50/125um OM2	DUPLICATE 3.0mm ZIPCORD	ORANGE	0.30dB	20dB	ELECTRIC IVORY	0.30dB	20dB	METALLIC FINISH
F6D6P-2M*Y		62.5/125um OM1		ORANGE	0.30dB	20dB	ELECTRIC IVORY	0.30dB	20dB	METALLIC FINISH
F9D6P-2M*Y		9/125um OS1		YELLOW	0.75dB	55dB	BLUE	0.75dB	55dB	METALLIC FINISH

\* - DENOTES PATCH CORD LENGTH, WHERE M = METERS AND F = FEET

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	OTH
R	06-05-07	MC		RELEASED TO PRODUCTION	02779-16				

FIBER OPTIC PATCH CORD FJ OPTI-PLUG TO ST CONFIGURATION CUSTOMER DRAWING										
				<b>PANDUIT</b> ™ CORP. TINLEY PARK, ILL 60477						
 THIRD ANGLE PROJECTION				ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.X) ±.03   (.XXX) ±.010   (.3) ±.01				DRAWING FILENAME M02779BJ_DC_00A.prt		
				DRAWN BY MC DATE 05-10-07 CHK'D				SCALE NONE PART NO. SEE TABLE		
								DRAWING NO. 02779-16 (SHT. 2 of 2)		SIZE <b>A</b>