

Industries

Solutions

Services

Software

**Products** 

**Partners** 

Support

About Us



-Search-

Entire Site

## Search Results

## Evaluate

- FAQ's
- How to Buy - Bill of Material
- Favorite Products List
- Locate Distributor

## Home > Product On-Line Catalog > Search Results >

Current refinements (click ≥ to remove) Search Tips @ ▼ Text Search: 'F9S3-4M3Y'

Your search criteria matched only one product, shown below

## F9S3-4M3Y



- Pass all TIA/EIA-568-B.3 performance requirements
- 100% factory inspected end face geometry in compliance with Telcordia GR-326-CORE, Issue 3
- Typical insertion loss per connection: 0.25dB
- UPC polished (55dB minimum return loss)
- Factory terminated and 100% tested for insertion loss and return loss
- Insertion loss and return loss data recorded for every singlemode patch cord
- Lifetime traceability of test data to a Q.C. number on each patch cord
- Highest quality flame retardant fiber optic cable with tight-buffered coating on each optical fiber.

Part Number	F9S3-4M3Y
RoHS Compliancy Status	Intended for use in fixed installations which are outside the scope of RoHS
Note	F9S3-4M3Y replaces F9S3-4M3
Part Description	SC to FC singlemode simplex patch cord (one SC connector on one end and one FC connector on the other end) - 9/125µm.
Product Type	Hybrid Patch Cords
Length (m)	3
Fiber Compatibility	9/125µm
Fiber Cable Size	3mm
Fiber Cable Type	Jacketed
Fiber Type	Singlemode
Cable Color	Yellow
Cable Type	Simplex
CE Compliant	No
Connector 1 Type	SC Connector
Connector 2 Type	FC Connector
End Configurations	SC to FC
Fiber Count	1
Flammability Rating	Riser (OFNR)
Pricing Description	PC SC TO FC 9µm Simpl 3m
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.