

Products

- Products Overview
- Product Search**
- Evaluate
 - FAQ's
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click  to remove) Search Tips  Within Results

Part Number > HSTTN150-CY

Your search criteria matched only one product, shown below

HSTTN150-CY



Neoprene DRY-SHRINK™ Heat Shrink Tubing in Reels

- For dry locations
- Highly flexible tubing
- Excellent chemical resistance especially to fuels and oils
- Highly flame retardant
- Material Type: Elastomer Neoprene Crosslinked
- Shrink Ratio*: 2:1
- Temperature Range: -94°F to 250°F (-70°C to 121°C)
- Voltage: 600V
- Mil Spec: AMSDTL-23053/1 Class 2

* Shrink Ratios are approximations refer to Min Expanded Max Recovered ID's

- For dry locations
- Highly flexible tubing

- Excellent chemical resistance especially to fuels and oils
- Highly flame retardant

Part Number	HSTTN150CY
RoHS Compliancy Status	Compliant
Part Description	Highly flexible Neoprene material offers excellent chemical resistance, especially to fuels and oils.
Material	Elastomer Neoprene CrossLinked
Color	Black
CSA Certified	No
Military Specification	AMS-DTL-23053/1 Class 2
Length (m)	30.5
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	100
Length Per Reel (m)	30.5
Max. Recovered I.D. (In.)	.875
Max. Recovered I.D. (mm)	21.8
Min. Expanded I.D. (In.)	1.50
Min. Expanded I.D. (mm)	38.1
Nominal Diameter (In.)	1.50
Nominal Diameter (mm)	38.1
Nominal Recovered Wall Thickness (In.)	.095
Nominal Recovered Wall Thickness (mm)	2.4
Pricing Description	Heat Shrink Thin Neoprene, 1 1/2"(38.1mm) Dia
Shrink Ratio	2:1
Temperature Range	-94°F to 250°F (-70°C to 121°C)
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.