

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFHSTTPN50438 ..
 - Part Drawings
 - PDFChlorinated..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'HSTTN175-CY'

Your search criteria matched only one product, shown below


HSTTN175-CY



Chlorinated Polyolefin DRY -SHRINK™ Heat Shrink Tubing in Reels

- Applications include insulating and protecting wires and cables
- Excellent chemical resistance especially to fuels and oils
- Voltage: 600 V
- Shrink ratio: 2:1*
- Mil Spec: AMSDTL-23053/1 Class 2
- Temperature range: -94°F to 250°F (-70°C to 121°C)
- For dry locations
- Material: Chlorinated Polyolefin. Note: HSTTN300 -QY is Elastomer Neoprene.

*Shrink Ratios are approximations; Refer to Min. Expanded Max. Recovered ID's

Part Number	HSTTN175CY
RoHS Compliancy Status	Compliant
Part Description	Highly flexible Neoprene material offers excellent chemical resistance, especially to fuels and oils.
Material	Chlorinated Polyolefin
Color	Black
CSA Certified	No
Military Specification	AMS-DTL-23053/1 Class 2
Length (ft.)	30.5
CE Compliant	No
Length Per Reel (ft.)	100
Length Per Reel (m)	30.5
Max. Recovered I.D. (In.)	1.00
Max. Recovered I.D. (mm)	25.4
Min. Expanded I.D. (In.)	1.75
Min. Expanded I.D. (mm)	44.5
Nominal Diameter (In.)	1.75
Nominal Diameter (mm)	44.5
Nominal Recovered Wall Thickness (In.)	0.107
Nominal Recovered Wall Thickness (mm)	2.7
Pricing Description	Heat Shrink Thin Neoprene, 1.75"(44.5mm) Dia
Shrink Ratio	2:1
Temperature Range	-94°F– 250°F (-70°C– 121°C)
Type	DRY-SHRINK Thin Wall Neoprene Heat Shrink
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.