

Conductor marking collar - SD-WMS 3 (CH) YE:O - 0825557:O


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marking collar, labeled with the capital letter: Letters, yellow, width: 3.2 mm, the dimensions of the replacement product differ from the previous product!

RoHS

Key Commercial Data

| | |
|------------------------|---|
| Packing unit | 200 pc |
| Minimum order quantity | 200 pc |
| GTIN |  4 046356 415293 |
| GTIN | 4046356415293 |

Technical data

| | |
|--|--------------------------------|
| Color | yellow |
| Flammability rating according to UL 94 | V0 |
| Components | Free from silicone and cadmium |

Ambient conditions

| | |
|-------------------|------------------|
| Temperature range | -30 °C ... 60 °C |
|-------------------|------------------|

Standards and Regulations

| | |
|--|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V0 |

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>