

# Conductor marking collar - SD-WMS 5 (CH)R YE - 0825955

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marking collar, yellow, Horizontal: Letters, mounting type: thread on, cable diameter range: 2.5 - 5 mm, lettering field size: 3.2 x 2.6 mm, the dimensions of the replacement product differ from the previous product!

The figure shows the article SD-WMS 5 (NEUTRAL)R YE

## Your advantages

- Easy and reliable conductor labeling with SD-WMS ... conductor marking collars
- Supplied in rolls
- Multi-character labels can be created by combining several pre-labeled individual collars



## Key Commercial Data

Packing unit	500 pc
Minimum order quantity	500 pc

## Technical data

### Dimensions

Length (b)	4.2 mm
Width (a)	3.2 mm
Height (c)	5.5 mm
Cable diameter	2.5 mm ... 5 mm

### Ambient conditions

Ambient temperature (operation)	-30 °C ... 60 °C
---------------------------------	------------------

### General

Note	Please specify the required marking with order: Minimum order per imprint: 1 packing unit
Color	yellow
Type	Profile
Components	Free from silicone and cadmium
Flammability rating according to UL 94	V0
Material	Polyvinyl chloride

# Conductor marking collar - SD-WMS 5 (CH)R YE - 0825955

## Technical data

### General

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Printing direction	Horizontal
Printing	Letters
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	96 h
Wipe resistance test result	Test passed
Salt spray test specification	DIN EN 60068-2-11:2000-02
Test duration	96 h
Salt spray testing result	Test passed
Alternating condensation climate with SO2 test specification	DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Wipe resistance of test specification inscriptions	DIN EN 61010-1 (VDE 0411-1):2011-07
Result	Test passed
Marking mounting type	thread on

### Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V0

### Environmental Product Compliance

REACH SVHC	Bis (2-ethylhexyl)phthalate (DEHP) 117-81-7
China RoHS	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>