

Polisher - VC-POLISHER/M FSMA - 1884982

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Polisher, metal, for repeated preparation of VARIOCON fiber optic ferrules



Polisher

Your advantages

Clear representation



Key Commercial Data

Packing unit	1 pc
GTIN	4 017918 171452
GTIN	4017918171452

Technical data

Mechanical characteristics

Weight	57 g

Standards and Regulations

Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	The products are suitable for applications in plant, controller, and electrical device engineering.



Polisher - VC-POLISHER/M FSMA - 1884982

Technical data

Standards and Regulations

When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
Assembled products may not be manipulated or improperly opened.
Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
When using the product in direct connection with third-party manufacturers, the user is responsible.
For operating voltages > 50 V AC, conductive connector housings must be grounded
Ensure that the protective or functional ground has been properly connected.
VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
Observe the corresponding technical data. You will find information: o On the product o On the packing label o In the supplied documentation o Online at phoenixcontact.com/products under the product
Only use tools recommended by Phoenix Contact
The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
Operate the connector only when it is fully plugged in.
Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
Observe the minimum bending radius of the cable. Lay the cable without twisting it.

Classifications

eCl@ss

eCl@ss 10.0.1	21019004
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	21019004
eCl@ss 8.0	21019004
eCl@ss 9.0	21019004

ETIM

ETHAGO	E0000700
I ETIM 2.0	I EC000796
1 - 1 - 1 - 1	



Polisher - VC-POLISHER/M FSMA - 1884982

Classifications

ETIM

ETIM 3.0	EC000796
ETIM 4.0	EC002609
ETIM 5.0	EC001699
ETIM 6.0	EC001699
ETIM 7.0	EC001699

UNSPSC

UNSPSC 6.01	27112301
UNSPSC 7.0901	27112301
UNSPSC 11	27112301
UNSPSC 12.01	27112301
UNSPSC 13.2	27112301

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com