

Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Used for mounting batteries that cannot be mounted on DIN rails.



Product Description

Mounting set, consisting of battery frame for universal wall mounting or surface mounting, 2 x cross dowel (M6) with collar, 2 x screw (M6 x 140), 2 x washer (6.4 x 12), 1 x battery retaining bracket with fixing bracket, and 4 x screw (M3 x 14).

Key Commercial Data

| | |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc |
| GTIN |  4 046356 933131 |
| GTIN | 4046356933131 |

Technical data

General

| | |
|------------------|----------------------|
| Net weight | 5 kg |
| Housing material | Steel, powder-coated |

Dimensions

| | |
|--------|--------|
| Width | 464 mm |
| Height | 201 mm |
| Depth | 205 mm |

Standards and Regulations

| | |
|-----------------------|----------------|
| Shock | IEC 60068-2-27 |
| Vibration (operation) | DNV GL |

Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27059290 |
| eCl@ss 4.0 | 27378000 |
| eCl@ss 4.1 | 27378000 |
| eCl@ss 5.0 | 27379100 |
| eCl@ss 5.1 | 27379100 |
| eCl@ss 6.0 | 27379200 |
| eCl@ss 7.0 | 27379201 |
| eCl@ss 8.0 | 27059290 |
| eCl@ss 9.0 | 27059290 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC002498 |
| ETIM 5.0 | EC002498 |
| ETIM 6.0 | EC002839 |
| ETIM 7.0 | EC002839 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 39121421 |
| UNSPSC 18.0 | 26111710 |
| UNSPSC 19.0 | 26111710 |
| UNSPSC 20.0 | 26111710 |
| UNSPSC 21.0 | 26111710 |

Approvals


Approvals

Approvals

DNV GL / BV / LR / ABS

Ex Approvals

Approval details

| | | | |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------|
| DNV GL |  | https://approvalfinder.dnvgl.com/ | TAA0000265 |
| Nominal voltage UN | 500 V | | |

Mounting set for securing the batteries - BATTERY MOUNTING CASE - 2320458

Approvals

| | |
|----------------------------|------|
| Nominal current IN | 41 A |
| mm ² /AWG/kcmil | 6 |

| | | | |
|----|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| BV |  | http://www.veristar.com/portal/veristarinfo/generalinfo/approved/approvedProducts/equipmentAndMaterials | 41516/A0 BV |
|----|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|

| | | | |
|----|-----------------------------------------------------------------------------------|---------------------------------------------------------|----------|
| LR |  | http://www.lr.org/en | 17/20032 |
|----|-----------------------------------------------------------------------------------|---------------------------------------------------------|----------|

| | | |
|-----|---------------------------------------------------------------------------------------------------------|------------------|
| ABS | http://www.eagle.org/eagleExternalPortalWEB/ | 15-GD1438179-PDA |
|-----|---------------------------------------------------------------------------------------------------------|------------------|

Accessories

Accessories

Battery unit

Energy storage - UPS-BAT/VRLA-WTR/24DC/26AH - 2320429



Energy storage device, lead AGM, VRLA technology, 24 V DC, 26 Ah, tool-free battery replacement, automatic detection, and communication with QUINT UPS-IQ

Energy storage - UPS-BAT/VRLA/24DC/38AH - 2320335



Energy storage device, lead AGM, VRLA technology, 24 V DC, 38 Ah, automatic detection, and communication with QUINT UPS-IQ