

Power cable - PLD E 608-CA-MS/4,0/FS AM - 2702305

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 3-position, PVC, orange RAL 2004, Plug straight, coding: black, on Socket straight, coding: black, cable length: 4 m

Product Description

The cable serves to connect multiple 600 class PLD enclosure lights in series.



Key Commercial Data

| | |
|--------------|---------------|
| Packing unit | 1 pc |
| GTIN | |
| GTIN | 4055626113302 |

Technical data

Dimensions

| | |
|-----------------|-----|
| Length of cable | 4 m |
|-----------------|-----|

Ambient conditions

| | |
|----------------------|-------------------|
| Degree of protection | IP20 |
| | IP40 (plugged in) |

General

| | |
|-----------------------------|----------|
| Rated current at 40°C | 16 A |
| Rated voltage | 250 V AC |
| Number of positions | 3 |
| Coding | black |
| Insertion/withdrawal cycles | 100 |

Material

| | |
|------------------|---------------|
| Material, knurls | not available |
|------------------|---------------|

Environmental Product Compliance

| | |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---------------------------------------------------------|

Power cable - PLD E 608-CA-MS/4,0/FS AM - 2702305

Technical data

Environmental Product Compliance

| | |
|--|------------------------------------------------|
| | No hazardous substances above threshold values |
|--|------------------------------------------------|

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27060311 |
| eCl@ss 5.0 | 27049000 |
| eCl@ss 5.1 | 27049000 |
| eCl@ss 6.0 | 27279200 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC002556 |
| ETIM 6.0 | EC001855 |
| ETIM 7.0 | EC001855 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 31251501 |
| UNSPSC 19.0 | 31251501 |
| UNSPSC 20.0 | 31251501 |
| UNSPSC 21.0 | 31251501 |

Accessories

Accessories

Power distributor

T distributor - PLD E 608-CO-MS/FS/FR - 2702310



T-distributor with 2 sockets and one connector for series connection, black, 3-pos.

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>