

SM Watch Crystals

- 4 Lead Surface Mount Tuning Fork Watch Crystals
- SM13S: 1.5x7x1.4mm, SM20S: 3.8x8.5x2.5mm



32.768 kHz

Standard Specifications

Calibration Frequency Tolerance ± 20 PPM at 25°C std,

 $SM20SD = \pm 10 PPM$

Operating Temperature Range (OTR) -40 to +85° C Frequency Stability over OTR

Calculate as: Frequency shift from 25°C to T°C in PPM


 $= -0.038 \text{ x } (T - 25)^2 \pm 10\%$

Load Capacitance 12.5 pF std, 6 pF avail. for SM20S only

Equivalent Series Resistance SM20S: 50 k ohm max, (ESR) SM13S: 65 k ohm max

 $\begin{array}{ll} \mbox{Drive Level} & 1 \mbox{μW maximum} \\ \mbox{Aging at 25} \mbox{$^{\circ}$C for the 1st year} & \pm 5 \mbox{ PPM maximum} \\ \mbox{Shunt Capacitance} & 1.0 \mbox{ pF to } 1.45 \mbox{ pF typical} \end{array}$

Part Numbering Guide



SM13S - 32.768K


Consult factory for available specifications. A special part number may be assigned.

Mechanical: inches (mm)


not to scale


Solder Pads


Due to part size and factory abilities, part marking may vary from lot to lot and may contain our part number or an internal code.

















Apr 2008

39

Packaging 16mm tape 8mm pitch



IMPORTANT NOTICE

Pletronics Incorporated (PLE) reserves the right to make corrections, improvements, modifications and other changes to this product at anytime. PLE reserves the right to discontinue any product or service without notice. Customers are responsible for obtaining the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to PLE's terms and conditions of sale supplied at the time of order acknowledgment.

PLE warrants performance of this product to the specifications applicable at the time of sale in accordance with PLE's limited warranty. Testing and other quality control techniques are used to the extent PLE deems necessary to support this warranty. Except where mandated by specific contractual documents, testing of all parameters of each product is not necessarily performed.

PLE assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using PLE components. To minimize the risks associated with the customer products and applications, customers should provide adequate design and operating safeguards.

PLE products are not designed, intended, authorized or warranted to be suitable for use in life support applications, devices or systems or other critical applications that may involve potential risks of death, personal injury or severe property or environmental damage. Inclusion of PLE products in such applications is understood to be fully at the risk of the customer. Use of PLE products in such applications requires the written approval of an appropriate PLE officer. Questions concerning potential risk applications should be directed to PLE.

PLE does not warrant or represent that any license, either express or implied, is granted under any PLE patent right, copyright, artwork or other intellectual property right relating to any combination, machine or process which PLE product or services are used. Information published by PLE regarding third-party products or services does not constitute a license from PLE to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from PLE under the patents or other intellectual property of PLE.

Reproduction of information in PLE data sheets or web site is permissible only if the reproduction is without alteration and is accompanied by associated warranties, conditions, limitations and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. PLE is not responsible or liable for such altered documents.

Resale of PLE products or services with statements different from or beyond the parameters stated by PLE for that product or service voids all express and implied warranties for the associated PLE product or service and is an unfair or deceptive business practice. PLE is not responsible for any such statements.

Contacting Pletronics Inc.

Pletronics Inc. Tel: 425-776-1880 19013 36th Ave. West Fax: 425-776-2760

Lynnwood, WA 98036-5761 USA E-mail: ple-sales@pletronics.com

URL: www.pletronics.com

Copyright © 2009 Pletronics Inc.