

ADSL LINE TRANSFORMERS

For Use With Texas Instruments' Chipsets



- Matched to Texas Instruments' AC5 chipset
- Excellent THD performance in a small footprint
- Designed to meet UL1950 and EN60950 for supplementary insulation requirements for working voltages up to 250Vrms

Electrical Specifications @ 25°C — Operating Temperature -40°C to +85°C

RoHS-5 Compliant Part No.	RoHS-6 Compliant Part No.	Mounting	Application	Turns Ratio	Interwinding Capacitance @ 100kHz, 0.1Vrms	OCL (1-4) w/(2-3) short	Leakage Inductance @ 100kHz, 0.1V (1-4) w/(2-3), (6-7), (5-8) short
B2205	B2205NL	SMT	CO	1:1.9 ±2%	16pf MAX	400µH ±5% @ 0.1V, 100kHz	7.5µH MAX
BX2375	—	SMT	CO; ADSL over ISDN	1:1.9 ±3%	22pf MAX	92.5µH ±5% @ 0.1V, 10kHz	3.2µH MAX



Additional Electrical Specifications

RoHS-5 Compliant Part No.	RoHS-6 Compliant Part No.	THD (100kHz, 5.3Vrms)	DC Resistance		Isolation Voltage (Vrms)	Longitudinal Balance @ 100kHz
			Line Side (1-4) w/(2-3) short	Chip Side (5-8) w/(6-7) short		
B2205	B2205NL	≤-80dB	≤1.10Ω MAX	≤1.10Ω MAX	1500	≤-60dB
BX2375	—	≤-80dB	≤0.65Ω MAX	≤0.37Ω MAX	1500	≤-60dB




NOTE: Transformers are shipped in trays unless Tape & Reel packaging is specified by adding the suffix "T" to the part number (i.e. B2205T and B2205NLT).

Mechanical

Schematic



SUGGESTED PAD LAYOUT



Weight 3.4 grams
 Tray75/tray
 Dimensions: $\frac{\text{Inches}}{\text{mm}}$
 Unless otherwise specified,
 all tolerances are $\pm \frac{.010}{0.25}$

For More Information:

Pulse Worldwide Headquarters

12220 World Trade Dr.
 San Diego, CA 92128
 U.S.A.
www.pulseeng.com
 TEL: 858 674 8100
 FAX: 858 674 8262

Pulse Europe

Einsteinstrasse 1
 D-71083 Herrenberg
 Germany
 Tel: 49 7032 7806 116
 Fax: 49 7032 7806 135

Pulse China Headquarters

No. 1
 Industrial District
 Changan, Dongguan
 China
 Tel: 86 769 85538070
 Fax: 86 769 85538870

Pulse North China

Room 1503
 XinYin Building
 No. 888 YiShan Rd.
 Shanghai 200233
 China
 Tel: 86 21 54643211/2
 Fax: 86 21 54643210

Pulse South Asia

150 Kampong Ampat
 #07-01/02
 KA Centre
 Singapore 368324
 Tel: 65 6287 8998
 Fax: 65 6280 0080

Pulse North Asia

No. 26
 Kao Ching Rd.
 Yang Mei Chen
 Taoyuan Hsien
 Taiwan, R. O. C.
 Tel: 886 3 4641811
 Fax: 886 3 4641911

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

© Copyright, 2006. Pulse Engineering, Inc. All rights reserved.

www.pulseeng.com

B985.B (6/06)