











FAN ACCESSORIES

Fan Power Cords - 07 Series

Four configurations of high quality fan power cords designed to be used with tubeaxial fans with a strain relief for added safety. UL and CSA rated at 7 amps/300 volts with special configurations such as daisy chain, special length, color and a power plug are available.

| A | | B | | C | | D | |
|-------------|-------------|----|----------|--------|-------------|---|--|
| Part Number | Cord Length | | Style | Figure | Cordage | PDF Drawings | |
| | mm | in | | | | | |
| 07100-12 | 305 | 12 | Straight | A | SPT-1(18/2) |  | |
| 07100-24 | 610 | 24 | Straight | A | SPT-1(18/2) |  | |
| 07100-36 | 915 | 36 | Straight | A | SPT-1(18/2) |  | |
| 07100-40 | 1016 | 40 | Straight | A | SPT-1(18/2) |  | |
| 07100-50 | 1270 | 50 | Straight | A | SPT-1(18/2) |  | |
| 07100-60 | 1524 | 60 | Straight | A | SPT-1(18/2) |  | |
| 07100-80 | 2034 | 80 | Straight | A | SPT-1(18/2) |  | |
| 07145-12 | 305 | 12 | 45° | B | SPT-1(18/2) |  | |
| 07145-24 | 610 | 24 | 45° | B | SPT-1(18/2) |  | |
| 07145-36 | 915 | 36 | 45° | B | SPT-1(18/2) |  | |

| | | | | | | |
|----------|------|----|--------|---|-------------|--------------------------|
| 07145-40 | 1016 | 40 | 45° | B | SPT-1(18/2) | <input type="checkbox"/> |
| 07145-50 | 1270 | 50 | 45° | B | SPT-1(18/2) | <input type="checkbox"/> |
| 07145-60 | 1524 | 60 | 45° | B | SPT-1(18/2) | <input type="checkbox"/> |
| 07145-80 | 2034 | 80 | 45° | B | SPT-1(18/2) | <input type="checkbox"/> |
| 07190-12 | 305 | 12 | 90° | C | SPT-1(18/2) | <input type="checkbox"/> |
| 07190-24 | 610 | 24 | 90° | C | SPT-1(18/2) | <input type="checkbox"/> |
| 07190-36 | 915 | 36 | 90° | C | SPT-1(18/2) | <input type="checkbox"/> |
| 07190-40 | 1016 | 40 | 90° | C | SPT-1(18/2) | <input type="checkbox"/> |
| 07190-50 | 1270 | 50 | 90° | C | SPT-1(18/2) | <input type="checkbox"/> |
| 07190-60 | 1524 | 60 | 90° | C | SPT-1(18/2) | <input type="checkbox"/> |
| 07190-80 | 2034 | 80 | 90° | C | SPT-1(18/2) | <input type="checkbox"/> |
| 07199-12 | 305 | 12 | T-Type | D | SPT-1(18/2) | <input type="checkbox"/> |
| 07199-24 | 610 | 24 | T-Type | D | SPT-1(18/2) | <input type="checkbox"/> |
| 07199-36 | 915 | 36 | T-Type | D | SPT-1(18/2) | <input type="checkbox"/> |
| 07199-40 | 1016 | 40 | T-Type | D | SPT-1(18/2) | <input type="checkbox"/> |
| 07199-50 | 1270 | 50 | T-Type | D | SPT-1(18/2) | <input type="checkbox"/> |
| 07199-60 | 1524 | 60 | T-Type | D | SPT-1(18/2) | <input type="checkbox"/> |
| 07199-80 | 2034 | 80 | T-Type | D | SPT-1(18/2) | <input type="checkbox"/> |

