

Priority keylock switch, 16.2 mm, rectangular collar, 1 NO, Gold, Solder terminal, 3 x 90°, latching, key removal position 0+1+2+3

DISCONTINUED


fields of application

- > Measurement-control-regulation
- > Signalling systems
- > Industrial robots

special features

- > max. 35 V
- > 100 mA

description

Depending on the key, different switch positions are permitted: Key 1 switches to lock position 1, key 2 to lock position 1 and 2, etc...

Scope of delivery: 2 x 90° → 2 keys, 3 x 90° → 3 keys.

technical data

> general

illuminated	No
Collar shape	rectangular
Operating temperature, min.	-25 °C
Operating temperature, max.	70 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	80 °C
Soldering time for manual soldering, max.	3 sec
Soldering temperature for manual soldering	350 °C
Soldering	Manual soldering
Packaging	Box
Packaging unit	2 pcs.
net weight	42 g

direct links

- > RAFI eCatalog

standard delivery time	On request
Operating life	50,000 Cycles
RoHS compliant	Yes
REACH compliant	Yes
MOQ order	2
> mounting diameters	
Mounting hole	16.2 mm
Mounting depth	39.5 mm
Installation height	7.5 mm
Outside dimension, length	24 mm
Outside dimension, width	18 mm
> mechanical data	
Actuation function	latching
Operating torque	1.8 Nm
Contact function	1 NO
Contact system	Bridge-sliding contact
Contact material	Gold
Key lock	Micromec
Key removal position	0+1+2+3
Rotating angle	3 x 90°
Fixing	Threaded ring
Terminal on the rear	Solder terminal
Solderability	Yes
> electrical data	
Rated voltage, min.	5 V
Rated voltage, max.	35 V
Rated current, min.	0.05 A
Rated current, max.	0.1 A