

LUMOTAST 75 IP40, keylock switch, round collar, 1 NC + 1 NO, Silver, Solder terminal, 90°, latching, key removal position 0



fields of application

- > Measurement-control-regulation
- > Mechanical and system engineering
- > Signalling systems



description

technical data

> general

| | |
|-------------------------------------------------------------|---------------|
| illuminated | No |
| Collar color | black |
| Collar shape | round |
| Operating temperature, min. | -25 °C |
| Operating temperature, max. | 70 °C |
| Storage temperature, min. | -40 °C |
| Storage temperature, max. | 80 °C |
| Packaging | Box |
| Packaging unit | 2 pcs. |
| standard delivery time | 3 weeks |
| Operating life | 50,000 Cycles |
| Degree of protection, front side, according to DIN EN 60529 | IP40 |
| RoHS compliant | Yes |
| REACH compliant | Yes |
| MOQ order | 2 |

> mounting diameters

| | |
|---------------------------|---------|
| Mounting hole | 16.2 mm |
| Mounting depth | 41.5 mm |
| Installation height | 7.5 mm |
| Outside dimension, length | 18 mm |


direct links

- > [RAFI eCatalog](#)

| | |
|-----------------------------|----------------------------|
| Outside dimension, width | 18 mm |
| Collar dimension | 18 mm |
| > mechanical data | |
| Actuation function | latching |
| Contact function | 1 NC + 1 NO |
| Contact system | Bridge-snap-action contact |
| Contact material | Silver |
| Locking position | 45 |
| Number of locking positions | 45 |
| Key removal position | 0 |
| Rotating angle | 90° |
| Fixing | Threaded ring |
| Terminal on the rear | Solder terminal |
| Solderability | Yes |
| > electrical data | |
| Rated voltage, min. | 12 V |
| Rated voltage, max. | 230 V |
| Rated current, min. | 0.05 A |
| Rated current, max. | 4 A |

drawings

Dimensioned drawing



Mounting hole drawing

