

See below: Approvals and Compliances

Stock-Check, Detailed request for product

Weblinks

Description

- pre-assembled cable
- Low Voltage DC Plug and Socket

- DC Plug: 2-pole , straight

Technical Data

Diameter	5.5 mm / 3.3 mm / 1.0 mm
Number of Poles	2-pole
Ratings DC	2A/13.5VDC
Dielectric Strength	500 VDC
Insulation Resistance	> 100 MΩ @ 500 VDC

-20 °C to 70 °C
Cable
1.8 m
2 x 0.3 mm ²
straight
5000 Insertions

pdf data sheet, html datasheet, General Product Information, Distributor-

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
(1)	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimensions [mm]



4840.5220

All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DC Plug/Socket	5.5	2-pole	Cable	4840.5220

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 200 Pcs

Mating Outlets/Connectors

Category / Description



DC Plug/Socket Overview complete

, solder terminal, Socket, 5.9 mm, 2-pole, DC Plug/Socket , PCB terminals, Socket, 6.0 mm, 2-pole, DC Plug/Socket DC Plug/Socket further types to 4840.5220 4840.2220 4840.2221