



## 113LABEL - LABEL, 1033-21 JEDEC113, 4x4, 100/ROLL

	<b>CAUTION</b> This bag contains <b>MOISTURE-SENSITIVE DEVICES</b>	<b>LEVEL</b> 
1. Calculated shelf life in sealed bag: 12 months at <math>-40^{\circ}\text{C}</math> and <math>-90\%</math> relative humidity (RH).		<small>If Blank, see adjacent bar code label</small>
2. Peak package body temperature _____ $^{\circ}\text{C}$		<small>If Blank, see adjacent bar code label</small>
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must		
a) Mounted within: _____ hours of factory		<small>If Blank, see adjacent bar code label</small>
conditions $\leq 30^{\circ}\text{C}/60\%$ .		
b) Stored at <math><10\%</math> RH.		
4. Devices require bake, before mounting if:		
a) Humidity Indicator Card is >10% when read at <math>23\pm 5^{\circ}\text{C}</math>		
b) 3a or 3b not met.		
5. If baking is required, devices may be baked for 48 hours at <math>125\pm 5^{\circ}\text{C}</math>.		
<small>Note: If device containers cannot be subjected to high temperature or shorter bake times are desired, reference IPC/JEDEC J-STD-033 for bake procedure.</small>		
Bag Seal Date: _____		<small>If Blank, see adjacent bar code label</small>
<small>Note: Level and body temperature defined by IPC/JEDEC J-STD-020</small>		

For use with dry packaging applications. Displays the warning symbol and message in accordance with IPC/JEDEC J-STD-033 (1999) and JEDEC113-B. 3M can pre-apply this label to bags.