

January 7, 1998

TEL:805-498-2111 FAX:805-498-3804 WEB:http://www.semtech.com

## AXIAL LEADED HERMETICALLY SEALED SUPERFAST RECTIFIER DIODE

- Very low reverse recovery time
- Hermetically sealed in Metoxilite fused metal oxide
- Low switching losses
- Low forward voltage drop
- Soft, non-snap off, recovery characteristics

## QUICK REFERENCE DATA

- $V_R = 50 - 150V$
- $I_F = 5.0A$
- $t_{rr} = 30nS$
- $V_F = 0.97V$

### ABSOLUTE MAXIMUM RATINGS (@ 25°C unless otherwise specified)

	Symbol	1N6079 5FF05	1N6080 5FF10	1N6081 5FF15	Unit
Working reverse voltage	$V_{RWM}$	50	100	150	V
Repetitive reverse voltage	$V_{RRM}$	50	100	150	V
Average forward current (@ 55°C, lead length 0.375")	$I_{F(av)}$	←———— 5.0 —————→			A
Repetitive surge current (@ 55°C in free air, lead length 0.375")	$I_{FRM}$	←———— 24 —————→			A
Non-repetitive surge current ( $t_p = 8.3mS$ , @ $V_R$ & $T_{jmax}$ )	$I_{FSM}$	←———— 175 —————→			A
Storage temperature range	$T_{STG}$	←———— -65 to +150 —————→			°C
Operating temperature range	$T_{OP}$	←———— -65 to +150 —————→			°C

### MECHANICAL

G4

DIM <sup>n</sup>	MM		INCHES		NOTE
	MIN	MAX	MIN	MAX	
A	3.4	4.6	.135	.180	-
B	22.9	33.0	.90	1.30	-
C	3.5	4.2	.140	.165	-
D	-	.80	-	.030	1
E	.91	1.07	.036	.042	-

NOTES:  
1. LEAD DIAMETER UNCONTROLLED OVER THIS REGION.

Weight = 0.039oz

These products are qualified to MIL-S-19500/503.

They can be supplied fully released as JAN, JANTX, and JANTXV versions.

These products are qualified in Europe to DEF STAN 59-61 (PART 80)/030 available to F and FX levels.

January 7, 1998

**ELECTRICAL CHARACTERISTICS** (@ 25°C unless otherwise specified)

	Symbol	1N6079 5FF05	1N6080 5FF10	1N6081 5FF15	Unit
Average forward current max. T <sub>A</sub> = 55°C for sine wave	I <sub>F(AV)</sub>	←—————	2.0	—————→	A
Average forward current max. T <sub>L</sub> = 70°C; L = 0" T <sub>L</sub> = 55°C; L = 3/8" for sine wave	I <sub>F(AV)</sub>	←—————	12.0	—————→	A
for square wave	I <sub>F(AV)</sub>	←—————	4.8	—————→	A
I <sup>2</sup> t for fusing (t = 8.3mS) max.	I <sup>2</sup> t	←—————	5.0	—————→	A
Forward voltage drop max. @ I <sub>F</sub> = 5.0A, T <sub>j</sub> = 25°C	V <sub>F</sub>	←—————	127	—————→	A <sup>2</sup> S
Reverse current max. @ V <sub>RWM</sub> , T <sub>j</sub> = 25°C	I <sub>R</sub>	←—————	0.97	—————→	V
@ V <sub>RWM</sub> , T <sub>j</sub> = 100°C	I <sub>R</sub>	←—————	10	—————→	μA
Reverse recovery time max. 0.5A I <sub>F</sub> to 1.0A I <sub>R</sub> . Recovers to 0.25A I <sub>RR</sub> .	t <sub>rr</sub>	←—————	500	—————→	μA
Junction capacitance typ. @ V <sub>R</sub> = 5V, f = 1MHz	C <sub>j</sub>	←—————	30	—————→	nS
		←—————	230	—————→	pF

**THERMAL CHARACTERISTICS**

	Symbol	1N6079 5FF05	1N6080 5FF10	1N6081 5FF15	Unit
Thermal resistance - junction to lead Lead length = 0.375"	R <sub>θJL</sub>	←—————	23.5	—————→	°C/W
Lead length = 0.0"	R <sub>θJL</sub>	←—————	5	—————→	°C/W
Thermal resistance - junction to amb. on 0.06" thick pcb. 1 oz. copper.	R <sub>θJA</sub>	←—————	75	—————→	°C/W

January 7, 1998




Fig 1. Forward voltage drop as a function of forward current




Fig 2. Maximum power versus lead temperature




Fig 3. Transient thermal impedance characteristic.




Fig 4. Typical junction capacitance as a function of reverse voltage.

January 7, 1998




Fig 5. Forward power dissipation as a function of forward current, for sinusoidal operation.




Fig 6. Forward power dissipation as a function of forward current, for square wave operation.




Fig 7. Maximum repetitive forward current as a function of pulse width at 55°C;  $R_{\theta JL} = 20 \text{ }^\circ\text{C/W}$ ;  $V_{RWM}$  during  $1 - \delta$ .




Fig 8. Maximum repetitive forward current as a function of pulse width at 100°C;  $R_{\theta JL} = 80 \text{ }^\circ\text{C/W}$ ;  $V_{RWM}$  during  $1 - \delta$ .