



Emergency pull-wire switch ZS 80

Features/Options:

- Metal enclosure
- 4 contacts
- Position indicator and integrated emergency-stop push-button
- Wire length up to 100 m
- Spring force variant: 100 N
- Lever for release and position indication
- Watertight collar
- Wire pull and breakage detection
- Indicator lamps for various voltages can be found in the chapter Accessories in the Appendix
- Corrosion-resistant version with high degree of protection IP 67 available - see chapter [/ ZS 80 KST IP67 Niro Extreme >](#)

Technical data

Applied standards	EN 60947-5-1, -5; EN ISO 13850; EN ISO 13849-1
Enclosure	aluminium die-cast, powder-coated
Cover	glass-fibre reinforced, shock-proof thermoplastic, self-extinguishing UL 94 V-0
Degree of protection	IP 67 to IEC/EN 60529
Contact material	silver
Switching elements	2 NC/2 NO, 3 NC/1 NO or 4 NC contacts, type Zb
Switching system	slow action, positive break NC contacts ⊖
Connection	2 x 4 pole terminal block
Cable cross-section	max. 2.5 mm ² (incl. conductor ferrules)
Cable entry	3 x M20 x 1.5
B _{10d} (10 % load)	200 000
T _M	max. 20 years
Rated impulse withstand voltage U _{imp}	2.5 kV
Rated operating isolation voltage U _i	250 V
Conventional thermal current I _{the}	2 A
Utilisation category	AC-15; DC-13
Rated operating current/voltage I _e /U _e	2 A/250 VAC; 0.25 A/230 VDC; 2 A/24 VDC
Short-circuit protection	2 A gG/gN fuse
Ambient temperature	-25 °C ... +70 °C
Mechanical life	> 100 000 operations
Indicator lamp	as option
Max. wire length	100 m

Errors and omissions excepted.



Emergency pull-wire switch ZS 80

Technical data

Approvals



Ordering details



Slow action
2 NC/2 NO contacts

Type
ZS 80 2Ö/2S WVD

Material no.
1177916



Slow action
3 NC/1 NO contact

Type
ZS 80 3Ö/1S WVD

Material no.
1178758




Slow action
4 NC contacts

Type
ZS 80 4Ö WVD

Material no.
1178759

Accessories



Compensation spring ZS 80 8804

Type
Compensation spring ZS 80

Material no.
1187933

Errors and omissions excepted.



Emergency pull-wire switch ZS 80

Accessories



Cable Tensioner System TS 65
5704

Type
Cable Tensioner System TS 65

Material no.
1186621



Tensioner

Type
Tensioner M6
Tensioner M8 stainless steel

Material no.
1033254
1033300



Indicator lamp glow lamp

Type
Indicator lamp glow lamp 24 VDC

Material no.
1164937



Indicator lamp 24 V

Type
Indicator lamp 24 VAC DC

Material no.
1348797



Indicator lamp Multi-LED red

Type
Indicator lamp Multi-LED RD 24 VDC
Indicator lamp Multi-LED RD 115 VAC
Indicator lamp Multi-LED RD 230 VAC

Material no.
1169219
1169221
1178917



Indicator lamp Multi-LED white

Type
Indicator lamp Multi-LED WH 24 VDC







Material no.
1169220

Errors and omissions excepted.



Emergency pull-wire switch ZS 80

Accessories

	Pull-wire	Type Pull-wire Ø 5 mm per metre Pull-wire stainless steel Ø 5 mm per metre	Material no. 1032984 1033297
	Pull-wire set	Type Complete pull-wire set, 5 m Complete pull-wire set, 10 m Complete pull-wire set, 15 m Complete pull-wire set, 20 m Complete pull-wire set, 25 m Complete pull-wire set, 30 m Complete pull-wire set, 40 m Complete pull-wire set, 50 m	Material no. 1041628 1041633 1041634 1041645 1041635 1041641 1041647 1041642
	Pulley 3388	Type Pulley	Material no. 1041765
	Wire clamp	Type Wire clamp 3 mm Wire clamp 3 mm stainless steel	Material no. 1033247 1033299
	Duplex wire clamp 3410	Type Duplex wire clamp	Material no. 1033248
	Egg-shaped wire clamp 3412	Type Egg-shaped wire clamp	Material no. 1181896

Errors and omissions excepted.



Emergency pull-wire switch ZS 80

Accessories



Wire thimble

Type
Wire thimble 3 mm
Wire thimble 3 mm stainless steel

Material no.
1033245
1172707



Eye bolt

Type
Eye bolt M8 x 70 with nut
Eye bolt BM8 x 70 with nut, stainless steel
Eye bolt BM10 x 40 with nut

Material no.
1170601
1189687
1032610



Eye bolt open

Type
Eye bolt open M10 x 70 with 2 nuts

Material no.
1279170