


- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



GBL



MECHANICAL DATA

Case: GBL

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - green compound (halogen-free)

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

Polarity: As marked

Weight: 2 g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	D2SB 05	D2SB 10	D2SB 20	D2SB 40	D2SB 60	D2SB 80
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800
Maximum average forward rectified current	I _{F(AV)}	2					
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	80					
Rating of fusing (t<8.3ms)	I ² t	26					
Maximum instantaneous forward voltage (Note 1) I _F = 2 A	V _F	1.1					
Maximum reverse current @ rated VR T _J =25 °C T _J =125 °C	I _R	10					
		500					
Typical thermal resistance	R _{θJL}	10					
	R _{θJA}	47					
Operating junction temperature range	T _J	- 55 to +150					
Storage temperature range	T _{STG}	- 55 to +150					

Note 1: Pulse test with PW=300µs, 1% duty cycle



EXAMPLE				
PREFERRED P/N	PART NO.	PACKING CODE	GREEN COMPOUND CODE	DESCRIPT
D2SB80 C2	D2SB80	C2		
D2SB80 C2G	D2SB80	C2	G	Green comp

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG. 1 MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL REVERSE CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT







FIG. 4 TYPICAL FORWARD CHARACTERISTICS





PACKAGE OUTLINE DIMENSIONS

GBL



DIM.	Unit (mm)		Unit (inc)	
	Min	Max	Min	Max
A	19.70	20.30	0.776	0.800
B	2.30	2.70	0.091	0.106
C	1.30	2.00	0.051	0.079
D	0.90	1.10	0.035	0.043
E	4.80	5.20	0.189	0.205
F	10.70	11.30	0.421	0.445
G	2.30	2.70	0.091	0.106
H	13.00	14.00	0.512	0.551
I	3.30	3.70	0.130	0.146
J	0.80	1.20	0.031	0.047
K	0.40	0.60	0.016	0.024

MARKING DIAGRAM



- P/N = Specific Device Code
- G = Green Compound
- YWW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, of any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to indemnify TSC for any damages resulting from such improper use or sale.

Document Number: DS_D1408052