

- Low profile package
- Ultra fast recovery time for high efficiency
- Moisture sensitivity: level 1, per J-STD-020
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



DO-214AA(SMB)

MECHANICAL DATA

Case : DO-214AA(SMB)

Molding compound, UL flammability classification rating 94V-0
 Base P/N with suffix "G" on packing code - halogen-free, RoHS compliant

Terminal : Matte tin plated leads, solderable per JESD22-B102
 Meet JESD 201 class 1A whisker test

Polarity : Indicated by cathode band

Weight : 0.09 gram (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)				
PARAMETER	SYMBOL	ESH2B	ESH2C	ESH2D
Maximum repetitive peak reverse voltage	V _{RRM}	100	150	150
Maximum RMS voltage	V _{RMS}	70	105	105
Maximum DC blocking voltage	V _{DC}	100	150	150
Maximum average forward rectified current	I _{F(AV)}	2		
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	60		
Maximum instantaneous forward voltage (Note 1) @ 2 A	V _F	0.90		
Maximum reverse current @ rated VR T _J =25 °C T _J =125 °C	I _R	2 50		
Maximum reverse recovery time (Note 2)	T _{rr}	20		
Typical junction capacitance (Note 3)	C _j	25		
Typical thermal resistance	R _{θJL} R _{θJA}	20 75		
Operating junction temperature range	T _J	- 55 to + 175		
Storage temperature range	T _{STG}	- 55 to + 175		

Note 1 : Pulse test with PW=300u sec, 1% duty cycle

Note 2: Reverse Recovery Test Conditions: I_F=0.5A, I_R=1.0A, I_{RR}=0.25A

Note 3: Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

(Note 1)	M4	SMB	3000 / 13" Plastic reel
----------	----	-----	-------------------------

Note 1: "x" defines voltage from 100V (ESH2B) to 200V (ESH2D)

EXAMPLE				
PREFERRED P/N	PART NO.	PACKING CODE	GREEN COMPOUND CODE	DESCRIPTION
ESH2D R5	ESH2D	R5		
ESH2D R5G	ESH2D	R5	G	Green compound

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL REVERSE CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT









FIG. 4 TYPICAL FORWARD CHARACTERISTICS






PACKAGE OUTLINE DIMENSIONS



DIM.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	1.95	2.10	0.077	0.083
B	4.25	4.75	0.167	0.187
C	3.48	3.73	0.137	0.147
D	1.99	2.61	0.078	0.103
E	0.90	1.41	0.035	0.056
F	5.10	5.30	0.201	0.209
G	0.10	0.20	0.004	0.008
H	0.15	0.31	0.006	0.012

SUGGESTED PAD LAYOUT



Symbol	Unit(mm)
A	2.3
B	2.5
C	4.3
D	1.8
E	6.8

MARKING DIAGRAM



- P/N = Specific Device Code
- G = Green Compound
- YW = Date Code
- F = Factory Code