

- Moisture sensitivity level: level 1, per J-STD-020
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



DO-214AC (SMA)

MECHANICAL DATA

Case: DO-214AC (SMA)

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - Green compound (halogen-free)

Base P/N with prefix "H" on packing code - AEC-Q101 qualified

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

with prefix "H" on packing code meet JESD 201 class 2 whisker test

Polarity: Indicated by cathode band

Weight: 0.06 g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	RS 1A	RS 1B	RS 1D	RS 1G	RS 1J	RS 1K
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800
Maximum average forward rectified current	I _{F(AV)}	1					
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	30					
Maximum instantaneous forward voltage (Note 1) @ 1 A	V _F	1.3					
Maximum reverse current @ rated VR T _J =25 °C T _J =125 °C	I _R	5 50					
Maximum reverse recovery time (Note 2)	T _{rr}	150				250	
Typical junction capacitance (Note 3)	C _j	10					
Typical thermal resistance	R _{θJC} R _{θJA}	32 105					
Operating junction temperature range	T _J	- 55 to +150					
Storage temperature range	T _{STG}	- 55 to +150					

Note 1: Pulse test with PW=300µs, 1% duty cycle

Note 2: Reverse Recovery Test Conditions: I_F=0.5A, I_R=1.0A, I_{RR}=0.25A

Note 3: Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

RS1x (Note 1)	Prefix "H"	F3	Suffix "G"	Folded SMA	1,800 / 7" P
		F2		Folded SMA	7,500 / 13" F
		F4		Folded SMA	7,500 / 13" P
		E3		Clip SMA	1,800 / 7" P
	E2	Clip SMA		7,500 / 13" P	
	N/A				

Note 1: "x" defines voltage from 50V (RS1A) to 1000V (RS1M)

EXAMPLE

PREFERRED P/N	PART NO.	AEC-Q101 QUALIFIED	PACKING CODE	GREEN COMPOUND CODE	DESC
RS1M R3	RS1M		R3		
RS1M R3G	RS1M		R3	G	Green
RS1MHR3	RS1M	H	R3		AEC-Q

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG. 1 FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL REVERSE CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT









FIG. 4 TYPICAL FORWARD CHARACTERISTICS






PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	1.27	1.58	0.050	0.062
B	4.06	4.60	0.160	0.181
C	2.29	2.83	0.090	0.111
D	1.99	2.50	0.078	0.098
E	0.90	1.41	0.035	0.056
F	4.95	5.33	0.195	0.210
G	0.10	0.20	0.004	0.008
H	0.15	0.31	0.006	0.012

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	1.68	0.066
B	1.52	0.060
C	3.93	0.155
D	2.41	0.095
E	5.45	0.215

MARKING DIAGRAM



- P/N = Specific Device Code
- G = Green Compound
- YW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, of any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to indemnify TSC for any damages resulting from such improper use or sale.

Document Number: DS_D1405049