



# TAOGLAS®



# Datasheet

## Meteor

**Part No:**  
*FW.90.SMA.M*

### **Description:**

Cellular 2G/3G/4G Flexible Whip Monopole Antenna

### **Features:**

Covers most Worldwide 4G/3G Cellular bands from 698-3500MHz

Also Covers CAT-M/NB-IoT Bands

Robust Inner Steel Core

TNC Male Connector

IP65 Rated Waterproof

RoHS & Reach Compliant

|                            |    |
|----------------------------|----|
| 1. Introduction            | 3  |
| 2. Specifications          | 4  |
| 3. Antenna Characteristics | 6  |
| 4. Radiation Patterns      | 8  |
| 5. Mechanical Drawing      | 14 |
| 6. Packaging               | 15 |
| <hr/>                      |    |
| Changelog                  | 16 |

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.



## 1. Introduction



The FW.90 is a flexible cellular whip antenna with IP65 housing. It has a wide response and high peak gain. Ideal for outdoor environments which require high gain, on both lower and upper bands. It's unique characteristic is it has stable peak gain on across common cellular bands used worldwide.

Typical Applications include:

- Smart Metering
- Remote Pipeline Monitoring
- Transportation

The FW.90 can be used with a Wall Mounting Bracket, and we have designed an L Shaped Bracket for use with the Whip Antenna, the part number for this option is WM.90.A.305111. Testing of the whip antenna on the bracket, in free-space, and on a reference ground-plane has been done to show the benefit of the L-bracket.

This antenna delivers wider coverage areas and more reliable connections for professional customers in the automotive, industrial industries. The whip is made up of a flexible inner steel core covered by TPU so extremely resistant to collisions and maintaining its original shape and RF performance. The whip and the connection internally to the bracket is IP65 waterproof.

The FW.90's connector can be customized subject to NRE, for further information please contact your regional Taoglas customer support team.


## 2. Specifications

| Electrical                 |                            |         |           |           |           |           |           |
|----------------------------|----------------------------|---------|-----------|-----------|-----------|-----------|-----------|
| Frequency (MHz)            | 698~896                    | 880~960 | 1710~1880 | 1850~1990 | 1710~2170 | 2570~2690 | 3300~3500 |
| <b>Peak Gain (dBi)</b>     |                            |         |           |           |           |           |           |
| Free Space                 | -1.7                       | -0.3    | 2.5       | 3.4       | 2.8       | 3.5       | 2.1       |
| With Ground plane(30x30cm) | -1.7                       | 2       | 4.7       | 5.1       | 4.6       | 4.7       | 4.3       |
| L - Bracket                | 0.7                        | 1.8     | 1.8       | 2.2       | 2.2       | 1.8       | 0.5       |
| <b>Average Gain (dB)</b>   |                            |         |           |           |           |           |           |
| Free Space                 | -5.8                       | -4.6    | -1.9      | -1.5      | -1.7      | -2.1      | -3.4      |
| With Ground plane(30x30cm) | -5.2                       | -3      | -1.7      | -1.4      | -1.7      | -1.8      | -1.4      |
| L - Bracket                | -4                         | -2.4    | -2.7      | -3        | -2.8      | -2.9      | -5.7      |
| <b>Efficiency</b>          |                            |         |           |           |           |           |           |
| Free Space                 | 26.4                       | 35.1    | 65.4      | 70.8      | 67.3      | 61.6      | 46        |
| With Ground plane(30x30cm) | 30.8                       | 50.3    | 67.3      | 71.8      | 67.9      | 65.5      | 67.2      |
| L - Bracket                | 43.3                       | 57.2    | 53.9      | 49.9      | 53.2      | 51.6      | 27.4      |
| Impedance                  | 50Ω                        |         |           |           |           |           |           |
| Polarization               | Linear                     |         |           |           |           |           |           |
| Radiation Pattern          | Omni                       |         |           |           |           |           |           |
| Input Power                | 50 W                       |         |           |           |           |           |           |
| Tested Power               | 10 W                       |         |           |           |           |           |           |
| Mechanical                 |                            |         |           |           |           |           |           |
| Height                     | 255mm                      |         |           |           |           |           |           |
| Base Diameter              | 16mm                       |         |           |           |           |           |           |
| Whip Diameter              | 4mm                        |         |           |           |           |           |           |
| Casing                     | ABS                        |         |           |           |           |           |           |
| Connector                  | TNC Male                   |         |           |           |           |           |           |
| Environmental              |                            |         |           |           |           |           |           |
| Temperature Range          | -40°C to 85°C              |         |           |           |           |           |           |
| Humidity                   | Non-condensing 65°C 95% RH |         |           |           |           |           |           |


| 5G/4G Bands |  |                      |         |
|-------------|--|----------------------|---------|
| Band Number | 5G NR / FR1 / LTE / LTE-Advanced / WCDMA / HSPA / HSPA+ / TD-SCDMA |                      |         |
|             | Uplink   | Downlink             | Covered |
| 1           | UL: 1920 to 1980   | DL: 2110 to 2170     | ✓       |
| 2           | UL: 1850 to 1910   | DL: 1930 to 1990     | ✓       |
| 3           | UL: 1710 to 1785   | DL: 1805 to 1880     | ✓       |
| 4           | UL: 1710 to 1755   | DL: 2110 to 2155     | ✓       |
| 5           | UL: 824 to 849   | DL: 869 to 894       | ✓       |
| 7           | UL: 2500 to 2570   | DL: 2620 to 2690     | ✓       |
| 8           | UL: 880 to 915   | DL: 925 to 960       | ✓       |
| 9           | UL: 1749.9 to 1784.9   | DL: 1844.9 to 1879.9 | ✓       |
| 11          | UL: 1427.9 to 1447.9   | DL: 1475.9 to 1495.9 | ✗       |
| 12          | UL: 699 to 716   | DL: 729 to 746       | ✓       |
| 13          | UL: 777 to 787   | DL: 746 to 756       | ✓       |
| 14          | UL: 788 to 798   | DL: 758 to 768       | ✓       |
| 17          | UL: 704 to 716   | DL: 734 to 746       | ✓       |
| 18          | UL: 815 to 830   | DL: 860 to 875       | ✓       |
| 19          | UL: 830 to 845   | DL: 875 to 890       | ✓       |
| 20          | UL: 832 to 862   | DL: 791 to 821       | ✓       |
| 21          | UL: 1447.9 to 1462.9   | DL: 1495.9 to 1510.9 | ✗       |
| 22          | UL: 3410 to 3490   | DL: 3510 to 3590     | ✓       |
| 23          | UL: 2000 to 2020   | DL: 2180 to 2200     | ✓       |
| 24          | UL: 1625.5 to 1660.5   | DL: 1525 to 1559     | ✗       |
| 25          | UL: 1850 to 1915   | DL: 1930 to 1995     | ✓       |
| 26          | UL: 814 to 849   | DL: 859 to 894       | ✓       |
| 27          | UL: 807 to 824   | DL: 852 to 869       | ✓       |
| 28          | UL: 703 to 748   | DL: 758 to 803       | ✓       |
| 29          | UL: -  | DL: 717 to 728       | ✓       |
| 30          | UL: 2305 to 2315   | DL: 2350 to 2360     | ✓       |
| 31          | UL: 452.5 to 457.5   | DL: 462.5 to 467.5   | ✗       |
| 32          | UL: -  | DL: 1452 – 1496      | ✗       |
| 35          |  | 1850 to 1910         | ✓       |
| 38          |  | 2570 to 2620         | ✓       |
| 39          |  | 1880 to 1920         | ✓       |
| 40          |  | 2300 to 2400         | ✓       |
| 41          |  | 2496 to 2690         | ✓       |
| 42          |  | 3400 to 3600         | ✓       |
| 43          |  | 3600 to 3800         | ✗       |
| 48          |  | 3550 to 3700         | ✗       |
| 66          | UL: 1710-1780  | DL: 2110-2200        | ✓       |
| 71          |  | 617 to 698           | ✗       |
| 74/75/76    |  | 1427 to 1518         | ✗       |
| 77          |  | 3300 to 4200         | ✗       |
| 78          |  | 3300 to 3800         | ✓       |
| 79          |  | 4400 to 5000         | ✗       |

## 3. Antenna Characteristics


### 3.1 Return Loss




### 3.2 Efficiency



### 3.3 Peak Gain




### 3.4 Average Gain



## 4. Radiation Patterns







### 4.1 Antenna Stand Alone






**XY Plane**

**XZ Plane**









4.2 Antenna with Ground plane (30\*30cm)




**XY Plane**


**XZ Plane**








### 4.3 Antenna with L-Bracket



### XY Plane



### XZ Plane



# 5. Mechanical Drawing (Units: mm)

|                      |   |                      |     |  |          |             |            |
|----------------------|---|----------------------|-----|--|----------|-------------|------------|
| 6                    | 5 | 4                    | 3   | 2  | 1        |             |            |
| ISO NO: EDW-11-8-263 |   | REV ZONE DESCRIPTION |     | ENG  | APPROVED | ISSUED DATE |            |
| <Release>            |   | △ A                  | ALL | Initial Design   | Jason    | Joanna      | 2011/06/08 |
|                      |   | △ B                  | F3  | Amend Dimensions   | Sandy    | Joanna      | 2012/03/13 |
|                      |   | △ C                  | B2  | Amend P/N(ECR-15-8-313)  | Kim      | Wayne       | 2015/12/07 |
|                      |   | △ D                  | ALL | Amend Dimensions & Tolerances<br>Amend Cap Material (ECR-17-8-088) | Haley    | Paul        | 2017/07/24 |


| Name                | P/N            | Material        | Finish | QTY |
|---------------------|----------------|-----------------|--------|-----|
| 1 Housing           | 000111K060002A | ABS             | Black  | 1   |
| 2 Flexible Whip     | 001111K000002A | Steel+PE Jacket | Black  | 1   |
| 3 Cap               | 000711C000002A | POM             | Black  | 1   |
| 4 Outer Body SMA(M) | 000611B000002A | Brass           | Black  | 1   |


|   |  |                            |                    |   |  |
|---|--|----------------------------|--------------------|---|--|
| UNLESS OTHERWISE SPECIFIED TOLERANCES ON: |  | DATE: 2011/06/08           | MAT'L:             | <br><small>antenna solutions TW Design Centre<br/>This drawing and its inherent design concepts are property of Taoglas. Not to be copied or given to third parties without the written consent of Taoglas.</small> | REV  |
| .X± 0.2                                   |  | UNIT: mm                   | FINISH:            |   | D  |
| XX± 0.5 .XX± 0.1                          |  | THIRD ANGLE PROJECTION     | SCALE: 1/1         |   | A  |
| X.± 0.3 .XXX± 0.05                        |  | APPROVED BY: Joanna        | CHECKED BY: Joanna | DRAWN BY: Jason   |  |
|   |  | CUSTOMERS SIGNATURE / DATE |                    |   | TITLE: FW.90 Penta-band Cellular Flexible Whip Antenna SMA(M) Straight |
|   |  | PART NO. : FW.90.SMA.M     |                    |   |  |

## 6. Packaging


1pc FW.90.SMA.M per PE Bag  
 Bag Dimension: 200\*100mm  
 Weight: 50g



50pcs FW.90.SMA.M per Large PE Bag  
 Bag Dimensions: 520\*360mm  
 Weight: 2.5Kg



200pcs FW.90.SMA.M per Carton  
 Dimensions: 360\*310\*160mm  
 Weight: 10.2Kg



Changelog for the datasheet

**SPE-11-8-142 - FW.90.SMA.M**

**Revision: K (Current Version)**

|                  |                          |
|------------------|--------------------------|
| Date:            | 2020-03-20               |
| Changes:         | Updated to show new data |
| Changes Made by: | Jack Conroy              |

**Previous Revisions**

**Revision: J**

|                  |                       |
|------------------|-----------------------|
| Date:            | 2019-08-16            |
| Changes:         | Updated to new format |
| Changes Made by: | Dan Cantwell          |

**Revision: E**

|                  |  |
|------------------|--|
| Date:            | 2014-03-21   |
| Changes:         | Updated spec to include 698~798MHz and also for 2570~2690Mhz |
| Changes Made by: | Aine Doyle   |

**Revision: I**

|                  |                             |
|------------------|-----------------------------|
| Date:            | 2017-08-04                  |
| Changes:         | Updated as per PCN-17-8-026 |
| Changes Made by: | Andy Mahoney                |

**Revision: D**

|                  |            |
|------------------|------------|
| Date:            | 2012-07-08 |
| Changes:         |            |
| Changes Made by: |            |

**Revision: H**

|                  |                   |
|------------------|-------------------|
| Date:            | 2017-05-02        |
| Changes:         | Update as per PCN |
| Changes Made by: | Andy Mahoney      |

**Revision: C**

|                  |                           |
|------------------|---------------------------|
| Date:            | 2012-03-23                |
| Changes:         | Packaging Details Updated |
| Changes Made by: | Made by Andy Mahoney      |

**Revision: G**

|                  |                      |
|------------------|----------------------|
| Date:            | 2017-04-04           |
| Changes:         | Added LTE Band Table |
| Changes Made by: | Peter Monahan        |

**Revision: B**

|                  |            |
|------------------|------------|
| Date:            | 2012-02-27 |
| Changes:         |            |
| Changes Made by: |            |

**Revision: F**

|                  |            |
|------------------|------------|
| Date:            | 2014-06-08 |
| Changes:         | Retested   |
| Changes Made by: | Aine Doyle |

**Revision: A (Original First Release)**

|         |            |
|---------|------------|
| Date:   | 2011-11-22 |
| Notes:  |            |
| Author: | Wayne Yang |





**TAOGLAS**®

[www.taoglas.com](http://www.taoglas.com)

