

+ RELAYS, CONTACTORS & SWITCHES

DIP & SIP SWITCHES



✓ Active

TE CONNECTIVITY (TE) **12P.DIP SWITCH ASSY** Alcoswitch | Alcoswitch DIP

1-5161390-2 TE Internal Number: 1-5161390-2

EU RoHS Compliant **EU ELV Compliant**

Product Type Switch Contact Mating Area Plating Material Tin Housing Color Natural Housing Material Nylon - GF Auto-Insertable No

PRODUCT DRAWING English

J 3D PDF

DOCUMENTATION

Product Drawings

DIP SWITCH SOLDER LEGS 3,2mm LONG

PDF

English

CAD Files

3D PDF

PDF

3D

Customer View Model 2D_DXF.ZIP

English



Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF

English

FEATURES

Please review product documents or contact us for the latest agency approval information.

+

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type Switch Sealed No Switch Type DIP Actuator Style Slide

Configuration Features

Number of Switches 12 Configuration (Pole-Throw) Single Pole - Single Throw Number of Positions 12

Body Features

Actuator Color Red

Contact Features

Contact Mating Area Plating Material Tin Auto-Insertable No Contact Base Material Phosphor Bronze Contact Mating Area Plating Thickness (µin) 98.42 Solder Tail Contact Plating Tin

Termination Features

Termination Post Length 3.2 mm [.1259 in]

Mechanical Attachment

Mounting Type Through Hole Mounting Angle Vertical

Housing Features



Housing Color Natural Housing Material Nylon - GF Centerline 2.54 mm [.1 in]

Dimensions

Length 33.02 mm [1.299 in] Height 8.5 mm [.334 in]

Usage Conditions

Operating Temperature Range (°C) -25 – 70

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Quantity 250 Packaging Method Box & Carton

Other

Comment Soldering in "off" position only

+

PRODUCT COMPLIANCE

Statement of Compliance

Statement of Compliance PDF

