

5148103 -1 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



5148103 -1

✓ [Active](#)

Eurocard Type B

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Mating Type = Plug
- ? Number of Positions = 32
- ? PCB Mount Angle = Right Angle
- ? Post Type = Solder Post
- ? Make First / Break Last

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [ASSEMBLY, PIN, EUROCARD, TYPE 1/2B, 32 POSITION, 2.6...](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? [Eurocard Connectors Types B,C,M,Q,R, & Enhanced Typ...](#) (PDF, English)

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Mating Type](#) = Plug
- ? [Number of Positions](#) = 32
- ? [PCB Mount Angle](#) = Right Angle
- ? [Post Type](#) = Solder Post
- ? [Make First / Break Last](#) = Yes
- ? [DIN Level](#) = II
- ? [Size](#) = Half
- ? [PCB Retention Feature](#) = No
- ? Color = Gray
- ? Comment = Refer to customer drawing for specific loading patterns.

Termination Related Features:

- ? [Termination \(Solder\) Post Length \(mm \[in\]\)](#) = 2.65 [0.104], 4.16 [0.164], 4.93 [0.194]

Body Related Features:

- ? [Contact Cross Section \(mm \[in\]\)](#) = 0.64 [.025] Sq.
- ? Rows Loaded = A, B

Contact Related Features:

- ? Contact Material = Brass

Housing Related Features:

- ? Housing Material = Polyester GF

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? [Flux - Tight Coating](#) = Without
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? Terminate To = Printed Circuit Board

Other:

- ? Brand = AMP