

**CAD Files:** ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version A)
- [3D Model](#) (IGES, Version A)
- [3D Model](#) (STEP, Version A)

[List all Documents](#)**Product Features** (Please use the Product Drawing for all design activity)**Product Type Features:**

- Product Type = Switch
- Tactile = Yes
- Configuration (Pole-Throw) = Single Pole - Single Throw
- Series = FSMJSM
- Mount Angle = Vertical
- Termination Type = Printed Circuit
- Actuator Style = Round
- Leg Style = Gullwing

**Electrical Characteristics:**

- Contact Rating = 50mA

**Body Features:**

- Mount Style = Surface Mount
- Actuator Length (mm [in]) = 9.40 [0.370]
- Actuator Profile = Extended
- Actuator Color = Pink
- Case Material = PPS
- Actuator Material = Nylon

**Contact Features:**

- Contact Plating = Silver
- Contact Base Material = Copper Alloy

**Housing Features:**

- Process Sealed = No
- Low Profile = No

**Configuration Features:**

- Operating Force
- Ganged = No
- ESD Grounded
- Actuator Force
- Number of Poles
- Illuminated
- Dust Proof
- Support Bracket
- Snap Action
- Switch Height

**Industry Standards:**

- [RoHS/ELV Compliance](#)
- [Lead Free Solder](#)  
Reflow solderable
- [RoHS/ELV Compliance](#)

**Conditions for Use:**

- Temperature Range

**Packaging Features:**

- Packaging Method

**Other:**

- Brand = Arrow
- Comment =

**Corporate Information**[Who We Are](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)**Quick Links**[Check Distributor Inventory](#)[Cross Reference](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)**Customer Support**[Email or Chat With Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage your Account](#)