



**+** RELAYS, CONTACTORS & SWITCHES

TACTILE SWITCHES



✓ Active

TE CONNECTIVITY (TE)

## FSM8JSMATR=TACT,SMT,T&R

Alcoswitch | Alcoswitch Tactile FSM JSM

1571563-9

TE Internal Number: 1571563-9

Alias ID: FSM8JSMATR

EU RoHS Compliant

EU ELV Compliant

**Actuator Style** Round

**Operating Function** NO

**Contact Base Material** Copper Alloy

**Contact Plating** Silver

**Dust Proof** No

[↓](#) **PRODUCT DRAWING**  
English

[↓](#) **3D PDF**

### DOCUMENTATION

Product Drawings

#### **MICRO MINIATURE PUSHBUTTON SWITCH FSM JSM**

PDF

**English**

CAD Files

#### **Customer View Model**

2D\_DXF.ZIP

**English**

#### **3D PDF**

PDF

**3D**

## Customer View Model

3D\_IGS.ZIP

English

## Customer View Model

3D\_STP.ZIP

English

## FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

---

### Product Type Features

**Illuminated** With

**Leg Style** Gull Wing

**Actuator Style** Round

**Dust Proof** No

**Product Type** Switch

---

### Configuration Features

**Snap Action** Without

**Tactile** Yes

**Operating Function** NO

**Support Bracket** Without

**Configuration (Pole-Throw)** Single Pole - Single Throw

**Number of Actuators** 1

**Ganged** With

**ESD Grounding Terminal** Without

**Tactile Feel** With

---

### Body Features

**Bushing Style** Unthreaded

**Case Material** PPS

**Actuator Color** Black

**Actuator Force** 160 g [ 5.648 oz ]

**Case Color** Brown

**Cover Material** Steel

**Actuator Material** PPS

**Actuator Profile** Extended

---

### Contact Features

**Contact Base Material** Copper Alloy

**Contact Plating** Silver

**Contact Current Rating (mA)** 50

---

### Termination Features

**Termination Type** Printed Circuit Board

---

### Mechanical Attachment

**Mounting Type** Surface Mount  
**Mounting Angle** With

---

Housing Features

**Low Profile** With  
**Process Sealed** No

---

Dimensions

**Switch Height** 9.5 mm [ .374 in ]  
**Button Width** 3.5 mm [ .138 in ]  
**Actuator Length** 5.9 mm [ .232 in ]

---

Usage Conditions

**Temperature Rating (°C)** Standard

---

Packaging Features

**Packaging Method** Loose Piece

---

Other

**Comment** (On) indicates momentary position.

---

## PRODUCT COMPLIANCE



Statement of Compliance

**Statement of Compliance**

PDF

---