Support Center

Innovation

Products

What can we help you find?

My Account

Home > Products > Relays > Product Feature Selector > Product Details

Resources

## 7022WD Product Details

Industries




About TE

TE Internal Number: 2-1437490-8

#### Product Highlights View All

- 7000 Electropneumatic Timing Industrial Series
- Input Voltage = 96 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 240 VAC
- Mounting Options = Mounting Bracket



Related Products

you're looking for?

**Find Similar Products** 

View Part in Product Feature Selector

Check for Tooling

Not quite the product

# Documents

Features

Active

Compliance

#### Please Note:

Use the Product Drawing for all design activity

Mechanical Attachment

Mechanical Attachment		
Mounting Options	Mounting Bracket	
Electrical Characteristics		
Input Voltage (VDC)	96	
Contact Rating	10A @ 240 VAC	
Termination Features		
Termination Type	Screw Terminal	
Dimensions		
Approx. Dimensions (L x W x H) (mm [in])	114.80 x 65.30 x 71.90 [4.523 x 2.572 x 2.832]	
Contact Features		
Delay Time	5 seconds to 50 seconds	
Type of Control	Knob	

 $\pm 5\%$ 

Configuration Features	
Contact - Arrangement	2 Form C, DPDT, 2 C/O
<b>Multiple Timing Ranges</b>	Without
Industry Standards	
Approved Standards	CE Approved, CSA Certified, UL Listed
RoHS/ELV Compliance	Not ELV/RoHS compliant
Lead Free Solder Processes	Not relevant for lead free process
Conditions for Usage	
Temperature Range (°C)	-30 - +75
Operation/Application	
Mode of Operation	Off-Delay
Other	
Series	7000 Electropneumatic Timing - Industrial
Brand	Agastat

## **Corporate Information**

Repeatability, Max.

About TE Investors News Room Supplier Portal

Terms & Conditions

Privacy Policy

Careers

Global Accessibility Statement

### Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings Product Compliance Support Center Site Map

## Customer Support

Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

#### **Keep Me Informed**







