

2174754-2 Product Details

Share | Print | Email



2174754-2

TE Internal Number: 2174754-2

Active

Pluggable Connectors, Cages & Accessories

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- QSFP+ Product Line
- Cage Assembly
- QSFP+ Application
- Cage Type = Ganged
- For Use With QSFP SMT Connector

[View all Features](#)

Quick Links

- ▶ Pricing & Availability
- ▶ Search for Tooling
- ▶ Product Feature Selector
- ▶ Contact Us About This Product

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • 1X4 CAGE ASSEMBLY, BEHIND BEZEL, W/ HEAT SINKS, COND... (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Line = QSFP+ • Product Type = Cage Assembly • Heat Sink Type = SAN • Heat Sink Style = Pin <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • PCB Mount = Double Sided (Belly-to-Belly) • Bezel Mounting Style = Behind Bezel <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Data Signal Rate (Gb/s) = Up to 64 <p>Termination Features:</p> <ul style="list-style-type: none"> • Termination Method to PC Board = Press-Fit <p>Dimensions:</p> <ul style="list-style-type: none"> • Heat Sink Height (mm [in]) = 6.50 [0.256] <p>Body Features:</p> <ul style="list-style-type: none"> • Heat Sink Finish = Electroless Nickel <p>Housing Features:</p> <ul style="list-style-type: none"> • Cage Type = Ganged 	<p>Configuration Features:</p> <ul style="list-style-type: none"> • Port Configuration = 1x4 • Heat Sink Included = Yes • Lightpipe = Without • EMI Containment = Elastomeric Gasket <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • For Use With = QSFP SMT Connector • Applies To = Printed Circuit Board <p>Operation/Application:</p> <ul style="list-style-type: none"> • Application = QSFP+ • Heat Sink Application = Yes <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



Feedback