


HEAT SHRINK TUBING



✓ Active

TE CONNECTIVITY

MFT-MT2000-NO.14-0-SP

MT2000-MFT

MFT-MT2000-NO.14-0-SP

TE Internal Number: CR8248-000

Alias ID: 2-1899603-9

Always EU RoHS/ELV Compliant

Wall Type **Single**

Resistant To **Fluids, Impact, Radiation Sterilization, Strain**

Product Source **US**

Packaging Method **Cut Piece, Spool, Stick**

Shrink Ratio **3:1**

No documentation available.

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features	Wall Type	Single
	Product Family	MT2000
Electrical Characteristics	Voltage (Max) (kV)	1
Body Features	Shrink Ratio	3:1
	Color	Black
	Flexibility	Semi-Rigid
	Material	Medical Grade Crosslinked Polyolefin
	Fluid Type	Medical Fluids, Water
Dimensions	Recovered Wall Thickness (Nominal)	.152 mm [.006 in]
	Recovered Inside Diameter (Max)	.203 mm [.008 in]
	Expanded Inside Diameter (Min)	0.356 mm [.014 in]
Usage Conditions	Resistant To	Fluids, Impact, Radiation Sterilization, Strain
	Recovery Temperature (°C)	140
	Operating Temperature Range (°C)	-55 – 175

Fluid Resistance

Moisture/Spray Protection, Splash Protection

Shrink Temperature (Min) (°C)

140

Packaging Features

Packaging Method

Cut Piece, Spool, Stick

Other

Product Source

US

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)