



External 192V 3U Rack/Tower Battery Pack for select Tripp Lite UPS Systems (BP192V12-3U)

MODEL NUMBER: BP192V12-3U





Description

Tripp Lite's BP192V12-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy-gauge cabling with high-current DC connectors for simple installation. Additional output connector allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SU12KRT4UHW, SU5000RT4U, SU5000RT4UHV, SU5000RT4UTF, SU6000RT4U, SU6000RT4UHV, SU6000RT4UHVG, SU6000RT4UHVHW, SU6000RT4UTF, SU6000RT4UTFHW, SU8000RT4U and other Tripp Lite UPS systems that specify the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Set of two input/output connectors allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- Includes heavy-gauge cabling with high-current DC connectors for simple installation

Specifications

OVERVIEW	
UPC Code	037332125903

Highlights

- Extends the runtime of expandable 192V DC Tripp Lite UPS Systems
- Included daisychain connector supports the addition of multiple compatible external battery packs
- Supports 3U rackmount installation; 4 post installation accessories included
- Options for 2 post rackmount and tower installation available

Package Includes

- BP192V12-3U external battery pack
- Mounting hardware
- · Warranty information
- Instruction manual



INPUT		
UPS Input Cord Length (ft.)	3	
UPS Input Cord Length (m)	0.9	
Input Phase	Single-Phase	
OUTPUT		
Overload Protection	50A DC output fuse	
BATTERY		
Expandable Battery Runtime	Includes a second input/output connector to daisy-chain multiple battery packs	
DC System Voltage (VDC)	192	
UPS Connection	Detachable cable with UPS specific DC connector (90 cm length, 8 gauge)	
Typical Battery Lifespan	4-6 years typical (North America)	
Expandable Runtime	Yes	
PHYSICAL		
External Battery Pack Form Factor	Rack/Tower	
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount	
Installation Form Factors Supported with Optional Accessories	2 post rackmount (2POSTRMKITHD); Tower (2-9USTAND)	
Material of Construction	Black steel cabinet	
Minimum Required Rack Depth (cm)	91.44	
Minimum Required Rack Depth (inches)	36	
Rack Height	3U	
Shipping Dimensions (hwd / cm)	27.94 x 58.42 x 83.82	
Shipping Dimensions (hwd / in.)	11.00 x 23.00 x 33.00	
Shipping Weight (kg)	88.00	
Shipping Weight (lbs.)	194.00	
Unit Dimensions (hwd / cm)	13,3 x 44,5 x 71,1	
Unit Dimensions (hwd / in.)	5.25 x 17.5 x 28	
Unit Weight (kg)	78.93	
Unit Weight (lbs.)	174.00	
WARRANTY		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies