

Cat6a 110-Style Punchdown RJ45 Keystone Jack, White, TAA

MODEL NUMBER: **N238-001-WH-6A**



Terminate your Cat6a cables at standard patch panels, surface-mount boxes or keystone wall plates.

Description

Strengthen your high-speed network with the N238-001-WH-6A Cat6a 110-Style Punchdown RJ45 Keystone Jack. Recommended for all Cat6a cabling environments, the keystone jack with a uniquely patterned printed circuit board is designed for 650 MHz performance and complies with EIA/TIA Cat6a connecting hardware specifications. The compact white casing snaps into any conventional patch panel, outlet box or wall plate. Dual-color-coded labeling is present for 568A and 568B (258A) wiring schemes. The N238-001-WH-6A meets UL-certified ANSI/TIA/EIA-568-B.2-10 Cat6a Permanent Link/Channel Identification Testing standards for Cat6a cabling installations. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

Cat6a Keystone Jack Strengthens Your High-Speed Network

- Compact casing snaps easily into standard patch panel, outlet box or wall plate
- Recommended for all Cat6a cabling environments
- Uniquely patterned printed circuit board designed for 650 MHz performance
- Dual-color-coded labeling for 568A/B (258A) wiring schemes
- UL-certified
- Meets all EIA/TIA Cat6a requirements

TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

Highlights

- Keystone design for use with standard data wall plate
- Dual-color-coded labeling for 568A/B (258A) wiring schemes
- Compatible with all Cat6a cables
- Meets all EIA/TIA Cat6a requirements
- TAA-compliant for GSA Schedule purchases

Package Includes

- N238-001-WH-6A Cat6a 110-Style Punchdown RJ45 Keystone Jack, White
- Shutter/dust cap



OVERVIEW	
UPC Code	037332204219
PHYSICAL	
Color	Gray; White
Shipping Dimensions (hwd / cm)	1.27 x 10.16 x 13.46
Shipping Dimensions (hwd / in.)	0.50 x 4.00 x 5.30
Shipping Weight (kg)	0.05
Shipping Weight (lbs.)	0.10
ENVIRONMENTAL	
Operating Temperature Range	14 to 140 F (-10 TO 60 C)
Storage Temperature Range	-40 to 154 F (-40 TO 68 C)
Relative Humidity	10% to 90% RH
CONNECTIONS	
Ports	1
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	110 IDC
PoE Type	Type 2 PoE+ (30W, IEEE 802.3at)
FEATURES & SPECIFICATIONS	
Technology	Cat5/5e; Cat6; Cat6a
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>