Fiber Optic - 10/100BaseT to 100BaseFX-ST Multimode Media Converter, 2km, 1310nm

MODEL NUMBER: **N784-001-ST**

Highlights

- Convert UTP Ethernet to Fiber
- Supports Auto MDI/MDI-X
- Half- or Full-Duplex Operation
- 10/100 Auto-sensing
- Supports Multimode 50/125 cable up to 2KM or 62.5/125 cable up to 550M

Package Includes

- 10/100 Multimode Media Converter, UTP - ST
- External Power Supply with NEMA 1-15P Plug (100-240V)
- Owner's Manual

Description

Tripp Lite's N784-001-ST, 10/100 Multimode Media Converter, is an economical way to extend the distance (up to 2Km) of network nodes by converting Cat5/6 UTP cables to Fiber Optic. The Media Converter features automatic MDI/MDI-X configuration, and the UTP port senses the network speed automatically as well. Dip switches allow half or full duplex operation on the fiber port. Power supplied by either AC-DC adapter, or USB connection (switch selectable). Tripp Lite

Features

- Connect 10BaseT/100BaseT UTP Ethernet to 100BaseFX Fiber Ethernet
- Auto MDI/MDI-X
- UTP port auto-senses network speed
- Switch selectable half or full duplex operation on the fiber port
- Fiber lengths up to 2Km
- 2 Power Choices - AC-DC Adapter or USB
- 5 LED Function lights
- Uses 62.5/125 or 50/125 Multimode cable
- 3.75"L x 2.75"W x 1"H
- Wavelength: 1310nm
- Supports Link Fault Pass-through (LFP) for easy tracing of network link failures
- Supports Multimode 50/125 cable up to 2KM or 62.5/125 cable up to 550M

Specifications

OVERVIEW	
UPC Code	037332130907
AC Adapter	Input: 100-240V

PHYSICAL	
Color	Black
Shipping Dimensions (hwd / cm)	23.50 x 5.51 x 12.50
Shipping Dimensions (hwd / in.)	9.25 x 2.17 x 4.92
Shipping Weight (kg)	0.43
Shipping Weight (lbs.)	0.94

CONNECTIONS	
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	ST DUPLEX (FEMALE)

FEATURES & SPECIFICATIONS	
Technology	Cat5/5e; Multimode

WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty