

at Serial Adapter (DB9 to DB25 F/M)

MODEL NUMBER: **P100-000-R**



Highlights

- Converts DB9 male serial connector to a DB25 male serial connector
- Fully shielded against EMI/RFI interference
- Gold Plated Connectors

System Requirements

- DB25F serial port on a PC or cable

Package Includes

- Serial Adapter Block DB9F to DB25M Gold Connectors

Description

Tripp Lite's serial adapter has gold plated connectors and will convert a DB9 male connector into a DB25 male connector. Lets a serial device with a DB9 connector attach to a PC with a DB25 port. PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress. 28 AWG stranded tinned copper conductors are individually insulated in polypropylene. This minimizes cross talk and ensures high-speed, error-free transmission. Clamshell retail packaging.

Features

- Connects a DB9 serial device to a DB25 cable or port
- Gold plated contacts and connectors for superior conductivity

Specifications

OVERVIEW	
UPC Code	037332011626
PHYSICAL	
Color	Black
Shipping Dimensions (hwd / cm)	13.97 x 11.43 x 3.18
Shipping Dimensions (hwd / in.)	5.50 x 4.50 x 1.25
Shipping Weight (kg)	0.10
Shipping Weight (lbs.)	0.22
CONNECTIONS	
Side A - Connector 1	DB9 (FEMALE)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Side B - Connector 1	DB25 (MALE)
FEATURES & SPECIFICATIONS	
Technology	DB25; Serial (RS232)
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>