

SmartRack Energy-Saving, Row-Based Server Rack Cooling Unit - 33,000 BTU, 208/240V, L6-30P Input Plug

MODEL NUMBER: SRCOOL33K



Self-contained rack cooling system provides up to 33,000 BTU of close-coupled cooling to high-density IT equipment.

Features

Get Highly Efficient, Reliable Cooling in a 42U Rack Form Factor The harder your data center, network closet or server room works, the more it heats up, leading to inefficient operation, weakened performance and raised cooling costs. To help prevent equipment shutdowns, malfunctions and failures caused by overheating and temperature fluctuations, the SmartRack® SRCOOL33K provides a close-coupled cooling solution in a 42U rack form factor that reduces energy use, lowers operating costs and simplifies installation.

Completely Self-Contained for Simplified and Less Expensive Installation and Maintenance The zero-maintenance SRCOOL33K with its intuitive LCD interface is easy to install and operate. You and your IT staff can install it yourself. No costly startup service, electrician or HVAC contractor is needed. A built-in evaporator eliminates condensation through the exhaust air stream, so no costly floor drain, water collection tank, external condenser, refrigerant piping, ductwork or plumbing is required.

Advanced Network Monitoring Keeps You in Touch 24/7 The pre-installed Java-free HTML5-based WEBCARDLX interface enables full remote monitoring, configuration, control and email notifications via secure web browser, SNMP, telnet or SSH. It supports 10/100 Mbps auto-sensing for optimum communication with an Ethernet network.

Energy-Saving Features Meant to Save You Money A row-based airflow path maximizes hot-aisle/cold-aisle efficiency and cooling predictability by delivering cold air high in the cold aisle and removing hot air in the hot aisle. The SRCOOL33K promotes temperature uniformity from 1U to 42U, allowing your equipment to perform at its peak and reduce power consumption and operating costs, and features an AC-driven rotary compressor.

One-Year Warranty and Environmentally Responsible Design The SRCOOL33K comes with a one-year warranty. It's manufactured in compliance with strict RoHS specifications and uses eco-friendly R410a refrigerant, reflecting Tripp Lite's commitment to environmental responsibility.

Highlights

- 33,000 BTU (9.7kW) of cooling power in self-contained, row-based, zero-maintenance unit
- Needs no costly electrician or HVAC contractor—can be fully installed by IT staff
- Expels condensation through exhaust air system—no floor drain or water collection tank required
- 10 ft. cord with NEMA L6-30P plug connects to 208/240V outlet
- Supports remote management 24/7 via pre-installed WEBCARDLX network interface

Applications

- Primary cooling of high-density equipment in a small server room, wiring closet or data center

Package Includes

- SRCOOL33K SmartRack Energy-Saving, Row-Based Server Rack Cooling Unit - 33,000 BTU, 208/240V
- Flexible air ducts
- Hot-exhaust removal tube
- Unloading ramps
- Unpacking guide
- Installation manual
- Owner's manual

Specifications



| OVERVIEW | |
|--|---|
| UPC Code | 037332172280 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 208V AC; 240V AC |
| Maximum Input Amps | 17.9 |
| Input Connection Type | L6-30P Input Cordset |
| Input Frequency | 60 Hz |
| Maximum Surge Amps | 23 |
| Input Cord Length (ft.) | 10 |
| Input Cord Length (m) | 3.05 |
| COOLING | |
| Cooling Type | Active |
| USER INTERFACE, ALERTS & CONTROLS | |
| Front Panel LEDs | Multi-line LCD control panel |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Steel/Aluminum |
| Shipping Dimensions (hwd / cm) | 214.38 x 65.02 x 114.05 |
| Shipping Dimensions (hwd / in.) | 84.40 x 25.60 x 44.90 |
| Shipping Weight (kg) | 285.76 |
| Shipping Weight (lbs.) | 630.00 |
| Unit Dimensions (hwd / cm) | 199.14 x 59.94 x 108.46 |
| Unit Dimensions (hwd / in.) | 78.4 x 23.6 x 42.7 |
| Unit Weight (kg) | 253.10 |
| Unit Weight (lbs.) | 558.00 |
| ENVIRONMENTAL | |
| Cooling Capacity | 33,000 BTU / 9.7 kW |
| SPECIAL FEATURES | |
| Dehumidifier | 3.35 L/HR |
| Compressor Type | AC ROTARY |
| Refrigerant | R410a (Environmentally friendly, Non ozone depleting) |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|---|
| Refrigerant Amount | 2.25 KG |
| Airflow | 1200 CFM |
| Amp Draw Nominal | Variable |
| Sound Level (Noise) | 60 dB |
| Air Exhaust Tube Length | 98 inches |
| Air Exhaust Tube Diameter | 9.84 inches |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to UL484; CSA, RoHS, FCC Class A |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>