

USB-C to 3.5 mm Stereo Audio Adapter - USB 2.0, Silver

MODEL NUMBER: U437-002











Connects a microphone and stereo headphones to the USB-C or Thunderbolt 3 port on your smartphone, MacBook, Chromebook or tablet.

Features

3.5 mm Audio Adapter Connects to Your Laptop's USB-C or Thunderbolt 3 PortThis USB Type-C to Stereo Audio Adapter allows you to connect a microphone and stereo earbuds or speakers to your computer, tablet, laptop, notebook, MacBook, Chromebook, Ultrabook or smartphone. Not only does this adapter allow you to bypass a defective sound card or 3.5 mm headphone jack, it also lets you connect to a device that offers only USB-C ports. The adapter features separate microphone (red) and headphone (green) jacks, instead of combining them into a single 3.5 mm audio connector as many notebooks do. Built-In USB-C Cable Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

Ready to Use Right Out of the Package The plug-and-play audio adapter requires no software, drivers or external power. The compact unit fits easily into a pocket, briefcase or laptop bag for connecting on the go.

Highlights

- Adds two 3.5 mm ports to a device that comes with no more than one stereo audio jack
- Connecting to a USB-C port lets you bypass a defective sound card or audio jack
- Compact aluminum housing fits into a laptop bag for easy listening anywhere
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Plug-and-play operation with no software required for speedy installation

Applications

- Listen to streaming music or sporting events through headphones, earbuds or speakers
- Connect a microphone to chat online via Skype or Facetime
- Record a podcast on your MacBook, Chromebook or other notebook computer

System Requirements

- PC, tablet, laptop, notebook,
 MacBook, Chromebook,
 Ultrabook or smartphone with
 USB-C or Thunderbolt 3 port
- Microphone, headphones, earbuds and/or speakers with
 3.5 mm plug
- Windows or Mac operating system

Package Includes



- U437-002 USB-C to Stereo
 Audio Adapter USB 2.0, Silver
- Quick Start Guide

Specifications

_		
OVERVIEW		
UPC Code	037332213822	
INPUT		
Built-In Cable Length (ft.)	0.66	
Built-In Cable Length (m)	0.2	
Built-In Cable Length (in.)	7.87	
Built-In Cable Length (cm)	20	
Bus Powered	Yes	
Product Length (in.)	10.75	
Product Length (cm.)	27.3	
Product Length (ft.)	0.9	
Product Length (m.)	0.27	
BATTERY		
Battery Charging (1.2 Port)	No	
PHYSICAL		
Cable Jacket Type	PVC	
Cable Outer Diameter (OD)	4.4mm +/- 0.15mm	
Color	Silver	
Material of Construction	Aluminum	
Unit Dimensions (hwd / cm)	1.3 x 2.8 x 4.6	
Unit Dimensions (hwd / in.)	0.51 x 1.10 x 1.81	
Unit Packaging Type	Polybag	
Unit Weight (kg)	0.04	
Unit Weight (lbs.)	0.082	
ENVIRONMENTAL		
Operating Temperature Range	32 ~ 158F (0 ~ 70C)	





Storage Temperature Range	-40 ~ 194F (-40 ~ 90C)	
Relative Humidity	20 ~ 80% RH	
CONNECTIONS		
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	(1) 3.5MM (FEMALE)	
Side B - Connector 2	(1) 3.5MM (FEMALE)	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
Audio Specification	Stereo	
Driver Required	No	
USB Power Delivery (PD) Charging Support	No	
Technology	Stereo Audio; USB; USB 2.0 (High Speed)	
CERTIFICATIONS		
Certifications	Tested to RoHS, REACH, FCC, CE	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies