



RESISTANCE @ +25°C = 20 Ω ± 20%
 MAXIMUM STEADY STATE CURRENT = 1.75 AMPS
 RESISTANCE @ MAXIMUM CURRENT = 0.60 Ω NOMINAL
 DIM "D" = 0.500" MAXIMUM
 DIM "T" = 0.300" MAXIMUM
 DIM "L" = 0.700" MINIMUM
 DIM "S" = 0.200" OR 0.310" (NOMINAL)

LEAD WIRE GAUGE = 20 AWG

SEE MANUFACTURING SPECIFICATION (LAYER 1)

"B"	DIM "S" WAS 0.310" NOMINAL	07/14/09	DD
"A"	DIM "L" WAS 1" MIN	07/02/09	DD
---	ISO RELEASE	07/02/09	DD
REV	REVISION RECORD	DATE	APP

SCALE	NONE	U.S. SENSOR CORP. 1832 W. COLLINS AVE. ORANGE, CA . 92867 714-639-1000 www.ussensor.com
DRAWN BY	T. SOMERVILLE	
DATE	02/19/93	
REV.	"B"	
LAYER	0 OF 2	
		INRUSH CURRENT LIMITER
		P/N ST20002B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[US Sensor:](#)

[ST20002B](#)