



- NOTE:
1. Rating: DC 5V 10mA
 2. Contact Resistance: 100mΩMAX
 3. Insulation Resistance: 100mΩMIN
 4. Soldering Temper: 260±5°/5s
 5. Mechanical Life: 100,000 cycles
 6. Ever Portion 80±50gf
 7. Push Portion 205±80gf
 8. Travel: -24° 0° +24°

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	5	5	Phosphor Bronze	Plating silver	
④	Base	1	1	Lcp		
③	Spring	1	1	Sus	Natural	
②	Cover	1	1	Sus	Natural	
①	Keystake	1	1	Ppa		

广东星坤科技股份有限公司

生效日期

文件工程章

日期

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
					ANGLAR ±5°
					L ≤ 4 ±0.2
					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	MULTI-FUNCTIONAL SWITCH
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.: TM-2011A
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT: 1.0g
			SHEET: 1/1
			REVISION: A0