


PCB Layout(Pattern side)

PART NO	H
TM-W07A-1	8.3
TM-W07A-2	8.5
TM-W07A-3	8.7
TM-W07A-4	9.3
TM-W07A-5	11.0
TM-W07A-6	12.3
TM-W07A-7	13.7



Circuit Diagram

NOTE:
 Rating: DC 30V 0.1A
 Operating Force: 40±10gf
 Lifetime: 100,000 Cycles

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Contact Spring	—	1	Phosphor Bronze	Plating silver	—
④	Terminal	—	4	Phosphor Bronze	Plating silver	—
③	Base	—	1	Nylon		—
②	Cover	—	1	Nylon		—
①	Keystake	—	1	Nylon		—

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

ANGLAR	±5°	XKIB	DSND		SCALE: N/A	MODEL TYPE: DETECT SWITCH
L ≤ 4	±0.2		DWN		VIEW:	PART NO.: TM-W07A-X
4 < L ≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.:
16 < L ≤ 63	±0.4		APPD		SIZE: A4	
L > 63	±0.5					
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT	SHEET	REVISIC	
				1/1	A0	